

# LED Insert B900 3K ON-OFF 60°

## INSERT B



- The linear LED inserts are designed for the professional replacement of conventional T5 or T8 fluorescent tubes. Thanks to comparable space requirements and magnetic mounting, they can be installed quickly and easily in older luminaires of various designs. Only LED drivers, LED modules and lenses from quality manufacturers are installed in the luminaire inserts. This achieves very good efficiency classes with outstanding quality and durability. The LED inserts from nevalux are often used for refurbishing luminaires in gymnasiums and warehouses, but also in offices and traffic zones.

861 x 32 x 24 mm



## LED Insert B900 3K ON-OFF 60°

INSERT B

## Technical Data

## IDENTIFICATION

|                |                 |
|----------------|-----------------|
| Variant        | Narrow beam 60° |
| Source         | woocommerce     |
| Product status | Normal          |
| Manufacturer   | Nevalux         |

## DIMENSIONS

Dimensions L x W x H **861 x 32 x 24 mm**

## ELECTRICAL

|                    |                             |
|--------------------|-----------------------------|
| Mains connection   | 220...240 V / 50 – 60 Hz    |
| Power              | 21.8 W                      |
| Replaceable driver | Yes                         |
| Type of wiring     | Suitable for through wiring |
| LED rated current  | 300 mA                      |

## SENSOR TECHNOLOGY

| With motion detector                                                                       | No                                                                                         |
|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| <p>  </p> | <p>  </p> |

Nevalux sensor technology On / Off

## LIGHTING TECHNOLOGY

|                             |          |
|-----------------------------|----------|
| Colour temperature          | 3000 K   |
| Colour rendering index      | 80-89    |
| Illuminant                  | LED      |
| Luminous flux               | 3459 lm  |
| Beam angle                  | 60°      |
| Luminaire luminous efficacy | 159 lm/W |

## LIFETIME

|                      |         |
|----------------------|---------|
| LED lifespan (25 °C) | 72000 h |
|----------------------|---------|

## SETTINGS

|                      |    |
|----------------------|----|
| DALI dimming         | No |
| With emergency light | No |

|                                       |     |
|---------------------------------------|-----|
| Suitable for light band configuration | Yes |
|---------------------------------------|-----|

## HOUSING &amp; MATERIAL

|                       |                 |
|-----------------------|-----------------|
| Protection class (IP) | IP20            |
| Protection class      | I               |
| Ambient temperature   | -25...55 °C     |
| Housing material      | Aluminum        |
| Cover material        | PMMA            |
| Mounting type         | lighting insert |
| Colour                | Aluminum        |

## SCOPE OF DELIVERY & WARRANTY

|                       |         |
|-----------------------|---------|
| Manufacturer warranty | 5 years |
|-----------------------|---------|

CERTIFICATES & EPREL

EPREL energy efficiency class **C**

# LED Insert B900 3K ON-OFF 60°

INSERT B

## Accessories

| ARTICLE NUMBER                                                                            | DESCRIPTION                      | CATEGORY           |
|-------------------------------------------------------------------------------------------|----------------------------------|--------------------|
|  221935   | Connect Smartlink HF3 Astra PSU  | Motion detector    |
|  220688   | Emergency Package 1h (250V/3.5W) | Emergency lighting |
|  221963   | LED Insert M-Set 3SK             | Mounting kit       |
|  221964  | LED Insert M-Set 3S              | Mounting kit       |
|  221968 | LED Insert B M-Set K             | Mounting kit       |

ORDERING INFORMATION

Art.-Nr.

221678

Typ

LED Insert B900 3K ON-OFF 60°

neva  
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss