

nefera P 4K

NEFERA C / P / W

neva
lux

1200 x 260 x 30 mm



nefera P 4K

NEFERA C / P / W

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		Direct/indirect ratio separately controllable		No
Source	woocommerce	Colour temperature	4000 K	Constant light output control		Yes
Product status	Normal	LED colour deviation	SDCM3			
Manufacturer	Nevalux	Colour rendering index	80-89	HOUSING & MATERIAL		
DIMENSIONS		Illuminant	LED	Protection class (IP)	IP20	
Dimensions L × W × H	1200 x 260 x 30 mm	Luminous flux	6000 lm (Down 4000, Up 2000)	Protection class	I	
Suspension length	1500 mm	Beam angle	Down 90°, Up 110°	Ambient temperature	-20...45 °C	
ELECTRICAL		Luminaire luminous efficacy	100 lm/W	Housing material	Aluminum	
Mains connection	200...240 V / 50 – 60 Hz	Glare value	UGR < 19	Cover material	Microprismatic acrylic glass	
Power	60 W	LIFETIME		Mounting type	Ceiling pendant	
Replaceable driver	Yes	LED lifespan (25 °C)	50000 h	Colour	White	
SENSOR TECHNOLOGY		SETTINGS		SCOPE OF DELIVERY & WARRANTY		
With motion detector	No	DALI dimming	Yes	Manufacturer warranty	5 years	
Nevalux sensor technology	DALI 2	With emergency light	No	CERTIFICATES & EPREL		
With light sensor	No	Suitable for light band configuration	No	EPREL energy efficiency class	F	

nefera P 4K

NEFERA C / P / W

Accessories

ORDERING INFORMATION

Art.-Nr. 220171

Typ nefera P 4K

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss