

IS 3360 MX Highbay DALI-2 Input Device - surface, sq.

neva
lux**MOTION DETECTOR**

EAN 4007841057374

65 x 95 x 95 mm



IS 3360 MX Highbay DALI-2 Input Device - surface, sq.

MOTION DETECTOR

EAN 4007841057374

Technical Data

IDENTIFICATION		SENSOR TECHNOLOGY		SETTINGS	
PU1 EAN	4007841057374	Max. mounting height	14,00 m	Twilight switch	Yes
Material number	110061488	Sensor technology	passive infrared	Twilight setting	2 – 1000 lx
SAP designation	BEWEGUNGSMELDER IS 3360 MX-E DALI2 AP WS	With motion detector	Yes	Base light function	No
Version	Motion detectors	Detection angle	360 °	Main light adjustable	No
Product name data sheet	IS 3360 MX Highbay DALI-2 Input Device - surface, sq.	Opening angle	180 °	Settings via	Bus
Product category	Motion detector	Sneak-under protection	Yes	With remote control	No
Discount group	B	Segment-by-segment masking	Yes	Twilight setting teach	No
Source	Steinel Excel	Electronic scalability	No	HOUSING & MATERIAL	
Product status	Normal	Mechanical scalability	No	Protection class (IP)	IP54
Manufacturer	Steinel	Radial range	Ø 14 m (154 m²)	Ambient temperature	from -20 up to 50 °C
DIMENSIONS		Tangential range	Ø 36 m (1018 m²)	Housing material	Plastic
Dimensions L x W x H	65 x 95 x 95 mm	Switching zones	1416 switching zones	Cover material	Plastic, opal
PU1 net weight	0.152	Mounting height	4,00 – 14,00 m	Cover material (scope of delivery)	shrouds
ELECTRICAL		Optimal mounting height	12 m	Mounting location	ceiling
Mains connection	12 – 22,5 V	Nevalux sensor technology	DALI 2	Application location	Indoors Outdoors
Supply voltage detail	DALI bus	CONNECTIVITY		Mounting type	Surface wiring
Switching output 1 potential-free	No	Networking	Yes	Material	Plastic
Control output DALI	Addressable/slave	Type of networking	Master/slave	Application room	high-bay warehouse sports hall Indoors
Max. current consumption per IEC 62386-101	24 mA	Networking via	DALI bus	Colour	white
Typical current consumption at 16 V input voltage	5 mA	Number of DALI participants	3	RAL colour	9003
Max. current consumption at 10 V input voltage in regular operation	7 mA	With bus coupler	Yes	SCOPE OF DELIVERY & WARRANTY	
		LIGHTING TECHNOLOGY		Manufacturer warranty	5 years
		Soft light start	No	Corner wall bracket included	No
		Constant light regulation	No	CERTIFICATES & EPREL	
				Certificates	DALI-2

IS 3360 MX Highbay DALI-2 Input Device - surface, sq.

MOTION DETECTOR

EAN 4007841057374

Illustrations

TECHNICAL DRAWINGS



65 x 95 x 95 mm

MOUNTING HEIGHT

4,00 – 14,00 m BEREICH	12 m OPTIMAL	14,00 m MAX
---------------------------	-----------------	----------------


IS 3360 MX Highbay DALI-2 Input Device - surface, sq.

EAN 4007841057374

MOTION DETECTOR

Wiring Diagrams

WIRING DIAGRAM 1



Circuit diagram

IS 3360 MX Highbay DALI-2 Input Device - surface, sq.


EAN 4007841057374

MOTION DETECTOR

Highlights



UV-resistant plastic



Large terminal compartment

IS 3360 MX Highbay DALI-2 Input Device - surface, sq.

MOTION DETECTOR

EAN 4007841057374

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841009151	Smart Remote	Accessory
 4007841056711	Schwarze Blende für IR-Sensoren Aufputz eckig	Accessory
 4007841056735	Schwarze Blende für IR-Sensoren Aufputz rund	Accessory

ORDERING INFORMATION

Art.-Nr.

057374

EAN

4007841057374

Typ

IS 3360 MX Highbay DALI-2 Input Device - surface, sq.

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss