

IR Quattro HD-2 24m COM2 - Surface wiring

neva
lux

PRESENCE DETECTOR

EAN 4007841064341

- Passive infrared presence detector with square 360° detection
- 5.200 switching zones for the finest detection
- Offers the largest detection range in our IR range
- 4 pyro sensors individually de-/activatable
- Sensitivity digitally adjustable
- Measures presence and brightness
- Temperature and humidity measurement with IP, KNX and DALI-2 IPD
- Setting and networking via Bluetooth
- Ideal for open-plan offices and classrooms

64 x 123 x 123 mm



IR Quattro HD-2 24m COM2 - Surface wiring

PRESENCE DETECTOR

EAN 4007841064341

Technical Data

IDENTIFICATION	
PU1 EAN	4007841064341
Material number	110067696
SAP designation	PRAESENZMELDER IR Q HD-2 COM2 AP WS
Version	Presence detector
Product name data sheet	IR Quattro HD-2 24m COM2 - Surface wiring
Product category	Presence detector
Discount group	P1
Source	Steinel Excel
Product status	Normal
Manufacturer	Steinel
DIMENSIONS	
Dimensions L x W x H	64 x 123 x 123 mm
PU1 net weight	0.276
ELECTRICAL	
Mains connection	220 – 240 V / 50 – 60 Hz
Switching output 1 resistive	2000 W
Fluorescent lamps ECG	1500 W
Fluorescent lamps uncompensated	1000 VA
Fluorescent lamps series-compensated	400 VA
Fluorescent lamps parallel-compensated	1000 VA
Switching output 1 low-voltage halogen lamps	2000 VA
LED lamps < 2 W	100 W
LED lamps > 2 W < 8 W	300 W
LED lamps > 8 W	600 W
Capacitive load in µF	176 µF
Own consumption	0,3 W

Switching output 1 number of LED/fluorescent lamps	8
Switching output 1 potential-free	No
Switching output 2 resistive	230 W
Switching output 2 potential-free	Yes
Maximum inrush current	800 A

SENSOR TECHNOLOGY	
Max. mounting height	10,00 m
Sensor technology	passive infrared
Detection angle	360 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	Yes
Mechanical scalability	Yes
Radial range	9 x 9 m (81 m²)
Tangential range	24 x 24 m (576 m²)
Switching zones	5200 switching zones
Mounting height	2,50 – 10,00 m
Presence range	9 x 9 m (81 m²)
Optimal mounting height	2,8 m
Nevalux sensor technology	BT SIG Mesh, On / Off

CONNECTIVITY	
Networking	Yes
Networking via	Bluetooth Mesh

LIGHTING TECHNOLOGY	
Soft light start	No
Continuous light	selectable
Constant light regulation	No

SETTINGS	
Twilight switch	Yes

Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Base light function	No
Main light adjustable	No
Functions	Group parameterisation Semi-/fully automatic Lighting scenario Manual ON / ON-OFF Neighbouring group function Normal / test mode
Settings via	Bluetooth Mesh App Potentiometers Smartphone
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL	
Protection class (IP)	IP54
Ambient temperature	from -20 up to 50 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	Surface wiring
Material	Plastic
Application room	lecture hall classroom open-plan office high-bay warehouse production facilities conference room / meeting room duty room recreation room changing room reception / lobby sports hall multi-storey / underground car park dining hall / staff restaurant Indoors
Colour	white
RAL colour	9003

SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
Corner wall bracket included	No


IR Quattro HD-2 24m COM2 - Surface wiring

PRESENCE DETECTOR

EAN 4007841064341

Illustrations

TECHNICAL DRAWINGS



64 x 123 x 123 mm

MOUNTING HEIGHT

2,50 – 10,00 m BEREICH	2,8 m OPTIMAL	10,00 m MAX
---------------------------	------------------	----------------


IR Quattro HD-2 24m COM2 - Surface wiring

EAN 4007841064341

PRESENCE DETECTOR

Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

IR Quattro HD-2 24m COM2 - Surface wiring

EAN 4007841064341

PRESENCE DETECTOR

Highlights



UV-resistant plastic

IR Quattro HD-2 24m COM2 - Surface wiring

PRESENCE DETECTOR

EAN 4007841064341

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841067335	Relais REL5A-Bluetooth	System components
 4007841067342	Tasterkoppler PC4-Bluetooth	System components

ORDERING INFORMATION

Art.-Nr.

064341

EAN

4007841064341

Typ

IR Quattro HD-2 24m COM2 - Surface wiring

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss