

PD IR 4360-24 COM1 - concealed black

neva
lux**MOTION AND PRESENCE DETECTOR**

EAN 4007841085070

- Our series for the common ranges
- Presence detector with 24 m motion detection and 7.5 m presence detection for switching light
- Ideal for offices, meeting rooms or passageways
- Includes insertable cover caps to limit the detection range
- Installation-friendly, thanks to round design and modular system with magnetic plug-in connection
- Key input and parallel switching of multiple sensors to expand the detection range
- External approval and measurement in accordance with sensNORM

109 x 74 mm



PD IR 4360-24 COM1 - concealed black

MOTION AND PRESENCE DETECTOR

EAN 4007841085070

Technical Data

IDENTIFICATION		Sensor technology		passive infrared		Main light adjustable		No	
PU1 EAN	4007841085070	With motion detector		Yes		Functions	Motions sensor	Light sensor	
Material number	110090125	Detection angle		360 °			Presence function	Presence	
SAP designation	PRAESENZMELDER PD IR 4360-24 COM1 UP SW	Sneak-under protection		Yes			detector logic	Semi-/fully automatic	Normal / test mode
Version	Motion and Presence Detector	Segment-by-segment masking		Yes			Potentiometer	Relay output	
Product name data sheet	PD IR 4360-24 COM1 - concealed black	Electronic scalability		No		Settings via	Remote control	Smart Remote	Potentiometers
Product category	Motion and Presence Detector	Mechanical scalability		No		With remote control			No
Discount group	P	Radial range		Ø 5.5 m (24 m²)		Twilight setting teach			Yes
Source	Steinel Excel	Tangential range		Ø 24 m (452 m²)		HOUSING & MATERIAL			
Product status	Normal	Switching zones		1436 switching zones		Protection class (IP)			IP20
Manufacturer	Steinel	Mounting height		2 – 10,00 m		Ambient temperature			from -20 up to 50 °C
DIMENSIONS		Presence range		Ø 7.5 m (44 m²)		Housing material			Plastic
Dimensions Ø × H	109 x 74 mm	Optimal mounting height		2,8 m		Cover material			Other
PU1 net weight	0.169	Nevalux sensor technology		On / Off		Cover material (scope of delivery)			shrouds
ELECTRICAL		CONNECTIVITY				Mounting location			ceiling
Mains connection	50 – 60 Hz	Networking		Yes		Application location			Indoors
Switching output 1 resistive	2000 W	Type of networking		Master/master		Mounting type			Concealed wiring
LED lamps > 8 W	500 W	Networking via		Cable		Material			Plastic
Capacitive load in µF	176 µF	LIGHTING TECHNOLOGY				Application room			one-person office function room / ancillary room
Switching output 1 number of LED/fluorescent lamps	50	Soft light start		Yes					Indoors warehouse
Maximum inrush current	800 A	Constant light regulation		No		Colour			black
SENSOR TECHNOLOGY		SETTINGS				RAL colour			9010
Max. mounting height	10,00 m	Twilight switch		Yes		SCOPE OF DELIVERY & WARRANTY			
		Twilight setting		2 – 1000 lx		Manufacturer warranty			5 years
		Time setting		5 s – 60 Min.		Corner wall bracket included			No


PD IR 4360-24 COM1 - concealed black

MOTION AND PRESENCE DETECTOR

EAN 4007841085070

Illustrations

TECHNICAL DRAWINGS



109 x 74 mm

MOUNTING HEIGHT

2 – 10,00 m BEREICH	2,8 m OPTIMAL	10,00 m MAX
------------------------	------------------	----------------


PD IR 4360-24 COM1 - concealed black

MOTION AND PRESENCE DETECTOR

EAN 4007841085070


Wiring Diagrams

WIRING DIAGRAM 1



Circuit diagram

WIRING DIAGRAM 2



Circuit diagram for interconnecting several sensors

PD IR 4360-24 COM1 - concealed black

MOTION AND PRESENCE DETECTOR

EAN 4007841085070

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841079543	Deckeneinbau-Adapter Deckeneinbau	Accessory
 4007841009151	Smart Remote	Accessory
 4007841592806	Nutzer Fernbedienung RC5	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory

ORDERING INFORMATION

Art.-Nr.

085070

EAN

4007841085070

Typ

PD IR 4360-24 COM1 - concealed black

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss