

ayana DALI C570 4K

AYANA

neva
lux

- Timeless simple acrylic glass luminaire in 3 different sizes
- Available in ceiling and pendant versions
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- Connect version available with light sensor (LS) or with motion detector and light sensor (PIR)
- For universal use for illumination of offices, schools, traffic zones, etc.
- Very high quality workmanship from Swiss manufacturing
- Sophisticated thermal management for long service life
- Variants with adjustable light color (Tunable White) to emulate the natural course of daylight

570 x 95 mm



ayana DALI C570 4K

AYANA

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		Direct/indirect ratio separately controllable	
Source	woocommerce	Colour temperature	4000 K		
Product status	Normal	LED colour deviation	SDCM3	HOUSING & MATERIAL	
Manufacturer	Nevalux	Colour rendering index	80-89	Protection class (IP)	IP20
DIMENSIONS		Illuminant	LED	Protection class	I
Dimensions Ø × H	570 x 95 mm	Luminous flux	6100 lm (Down 5250, Up 850)	Ambient temperature	-20...45 °C
ELECTRICAL		Beam angle	105°	Housing material	Steel
Mains connection	200...240 V / 50 – 60 Hz	Luminaire luminous efficacy	122 lm/W	Cover material	Acrylic glass opal
Power	51 W	Glare value	UGR < 21	Mounting type	Ceiling / wall surface-mounted
Replaceable driver	Yes	LIFETIME		Colour	White
Type of wiring	Suitable for through wiring	LED lifespan (25 °C)	70000 h	SCOPE OF DELIVERY & WARRANTY	
SENSOR TECHNOLOGY		SETTINGS		Manufacturer warranty	5 years
With motion detector	No	DALI dimming	Yes	CERTIFICATES & EPREL	
Nevalux sensor technology	DALI 2, On / Off	With emergency light	No	EPREL energy efficiency class	E
With light sensor	No				

ayana DALI C570 4K

AYANA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221104	ayana Diffusor 570 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting

ORDERING INFORMATION Art.-Nr.221168 Typayana DALI C570 4K	nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss
--	--