

MD IR D180 COM1 - white

MOTION DETECTOR

neva
lux

EAN 4007841066109

- formerly IS 180 digi HD now MD IR D180
- the first digitally adjustable infrared sensor for outdoor use
- flat rectilinear design for optimal adaptation to mounting location
- lens integrated in the product outside the viewing area
- detection quality is equally good in the detection area, regardless of the direction of walking
- 9 detection areas digitally adjustable
- all settings are easily made via Bluetooth using the STEINEL Connect App

42 x 116 x 116 mm



MD IR D180 COM1 - white

EAN 4007841066109

MOTION DETECTOR

Technical Data

IDENTIFICATION	
PU1 EAN	4007841066109
Material number	110072733
SAP designation	BEWEGUNGSMELDER MD IR D180 COM1 WS
Version	Motion detectors
Product name data sheet	MD IR D180 COM1 - white
Product category	Motion detector
Discount group	B
Source	Steinel Excel
Product status	Normal
Manufacturer	Steinel
DIMENSIONS	
Dimensions L x W x H	42 x 116 x 116 mm
PU1 net weight	0.25
ELECTRICAL	
Mains connection	220 – 240 V / 50 – 60 Hz
Switching output 1 resistive	2000 W
Fluorescent lamps ECG	500 W
Fluorescent lamps uncompensated	1000 VA
Fluorescent lamps series-compensated	400 VA
Fluorescent lamps parallel-compensated	400 VA
Switching output 1 low-voltage halogen lamps	2000 VA
LED lamps < 2 W	100 W
LED lamps > 2 W < 8 W	250 W
LED lamps > 8 W	500 W
Capacitive load in µF	176 µF

Own consumption	0,6 W
Switching output 1 potential-free	No
Maximum inrush current	10 A
SENSOR TECHNOLOGY	
Max. mounting height	2,50 m
Sensor technology	passive infrared
With motion detector	Yes
Detection angle	180 °
Opening angle	90 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	Yes
Mechanical scalability	No
Radial range	r = 6 m (57 m²)
Tangential range	r = 9 m (127 m²)
Mounting height	1,80 – 2,5 m
Optimal mounting height	2 m
Nevalux sensor technology	BT SIG Mesh, On / Off
CONNECTIVITY	
Networking	Yes
Networking via	Bluetooth Mesh
LIGHTING TECHNOLOGY	
Soft light start	No
Continuous light	selectable
Constant light regulation	No
SETTINGS	
Twilight switch	Yes

Twilight setting	2 – 1000 lx
Time setting	5 s – 60 Min.
Base light function	No
Main light adjustable	No
Functions	Motions sensor Adjustable fade time when switching on and off Capture zone definition Feedback indicator Night economy mode Normal / test mode Neighbouring group function Relay output Light sensor
Settings via	Smartphone Tablet Bluetooth Mesh App
With remote control	No
Twilight setting teach	Yes
HOUSING & MATERIAL	
Protection class (IP)	IP54
Ambient temperature	from -20 up to 40 °C
Mounting location	wall
Application location	Outdoors
Mounting type	Surface wiring
Material	Plastic
Application room	outdoors garden front door courtyard & driveway all round the building terrace / balcony corridor / aisle Indoors
Colour	white
RAL colour	9003
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
Corner wall bracket included	No


MD IR D180 COM1 - white

MOTION DETECTOR

EAN 4007841066109

Illustrations

TECHNICAL DRAWINGS



42 x 116 x 116 mm

MOUNTING HEIGHT

1,80 – 2,5 m BEREICH	2 m OPTIMAL	2,50 m MAX
-------------------------	----------------	---------------


MD IR D180 COM1 - white

EAN 4007841066109

MOTION DETECTOR

Wiring Diagrams

WIRING DIAGRAM 1




Master circuit diagram with switched luminaire

MD IR D180 COM1 - white


EAN 4007841066109

MOTION DETECTOR

Highlights



UV resistant material



Operatable via app

MD IR D180 COM1 - white

MOTION DETECTOR

EAN 4007841066109

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841067335	Relais REL5A-Bluetooth	System components
 4007841067342	Tasterkoppler PC4-Bluetooth	System components

ORDERING INFORMATION

Art.-Nr.

066109

EAN

4007841066109

Typ

MD IR D180 COM1 - white

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss