

aluna connect LS P910 TW

ALUNA

neva
lux

910 x 118 mm



aluna connect LS P910 TW

ALUNA

Technical Data

IDENTIFICATION		CONNECTIVITY			
Source	woocommerce	With radio network control	Yes	Direct/indirect ratio separately controllable	No
Product status	Normal	LIGHTING TECHNOLOGY		With program-controlled lighting control	Yes
Manufacturer	Nevalux	Colour temperature	3000...5600 K	Constant light output control	Yes
DIMENSIONS		LED colour deviation	SDCM3	HOUSING & MATERIAL	
Dimensions Ø × H	910 x 118 mm	Colour rendering index	80-89	Protection class (IP)	IP20
Suspension length	2000 mm	Illuminant	LED	Protection class	I
ELECTRICAL		Luminous flux	9800 lm (Down 8430, Up 1370)	Ambient temperature	-20...45 °C
Mains connection	200...240 V / 50 – 60 Hz	Beam angle	105°	Housing material	Steel
Power	78 W	Luminaire luminous efficacy	126 lm/W	Cover material	Acrylic glass opal
Replaceable driver	Yes	Glare value	UGR < 21	Mounting type	Ceiling pendant
Type of wiring	Suitable for through wiring	LIFETIME		Colour	White
SENSOR TECHNOLOGY		LED lifespan (25 °C)	70000 h	SCOPE OF DELIVERY & WARRANTY	
With motion detector	No	SETTINGS		Manufacturer warranty	5 years
Nevalux sensor technology	Smartlink, BT SIG Mesh	DALI dimming	Yes	CERTIFICATES & EPREL	
With light sensor	Yes	With emergency light	No	EPREL energy efficiency class	D

aluna connect LS P910 TW

ALUNA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221105	ayana Diffusor 850 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221366	Connect RTC	Real-time clock
 221570	Connect TK2 BLM	Pushbutton interface
 221846	aluna Color RAL_NCS_Ø910	Other
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

222039

Typ

aluna connect LS P910 TW

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss