

imani B1200 HO 4K DALI

IMANI CONNECT

neva
lux

- The universal trunking insert imani from nevalux is designed for professional refurbishment of existing trunking with T5 or T8 fluorescent tubes. The luminaire uses the existing trunking installation including existing through-wiring. Old light modules can be replaced with new modules easily, quickly and without tools. The insert fits most trunking systems available on the market.

1225 x 65 x 30 mm



imani B1200 HO 4K DALI

IMANI CONNECT

Technical Data

IDENTIFICATION			
Source	woocommerce	Nevalux sensor technology	DALI 2
Product status	Normal	With light sensor	No
Manufacturer	Nevalux	LIGHTING TECHNOLOGY	
DIMENSIONS		Colour temperature	4000 K
Dimensions L x W x H	1225 x 65 x 30 mm	LED colour deviation	SDCM3
PU1 net weight	1.4	Colour rendering index	80-89
ELECTRICAL		Illuminant	LED
Mains connection	200...240 V / 50 – 60 Hz	Luminous flux	6611 lm
Power	52 W	Beam angle	105°
Replaceable driver	Yes	Luminaire luminous efficacy	127 lm/W
Type of wiring	Suitable for through wiring	Glare value	UGR < 24
LED rated current	350 mA	LIFETIME	
Maximum number of luminaires per circuit breaker	C10: 21x, C16: 35x, B10: 13x, B16: 21x	LED lifespan (25 °C)	50000 h
SENSOR TECHNOLOGY		SETTINGS	
With motion detector	No	DALI dimming	Yes
		With emergency light	No
		Suitable for light band configuration	Yes
		HOUSING & MATERIAL	
		Protection class (IP)	IP40
		Protection class	I
		Ambient temperature	-20...45 °C
		Housing material	Aluminum
		Cover material	Diffusor opal
		Mounting type	Use in continuous row
		Colour	White
		SCOPE OF DELIVERY & WARRANTY	
		Manufacturer warranty	5 years
		CERTIFICATES & EPREL	
		EPREL energy efficiency class	D

imani B1200 HO 4K DALI

IMANI CONNECT

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220688	Emergency Package 1h (250V/3.5W)	Emergency lighting
 221476	imani APG1200	Surface mount housing

ORDERING INFORMATION

Art.-Nr.

221494

Typ

imani B1200 HO 4K DALI

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss