

HF 360 DALI-2 Input Device - concealed

neva
lux**PRESENCE DETECTOR**

EAN 4007841057480

56 x 120 x 120 mm



HF 360 DALI-2 Input Device - concealed

PRESENCE DETECTOR

EAN 4007841057480

Technical Data

IDENTIFICATION		SENSOR TECHNOLOGY		LIGHTING TECHNOLOGY	
PU1 EAN	4007841057480	Max. mounting height	3,50 m	Soft light start	No
Material number	110061501	Sensor technology	High frequency	Constant light regulation	No
SAP designation	PRAESENZMELDER HF 360 DALI2 UP WS	Transmission power	< 1 mW	SETTINGS	
Version	Presence detector	HF technology	5,8 GHz	Twilight switch	Yes
Product name data sheet	HF 360 DALI-2 Input Device - concealed	Detection	also through glass, wood and stud walls	Twilight setting	10 – 1000 lx
Product category	Presence detector	Detection angle	360 °	Base light function	No
Discount group	P	Opening angle	140 °	Main light adjustable	No
Source	Steinel Excel	Sneak-under protection	Yes	Settings via	Bus
Product status	Normal	Segment-by-segment masking	Yes	With remote control	No
Manufacturer	Steinel	Electronic scalability	Yes	Twilight setting teach	No
DIMENSIONS		Mechanical scalability	No	HOUSING & MATERIAL	
Dimensions L × W × H	56 x 120 x 120 mm	Range detail	1 or 2 detection directions can be masked out by stickers for adjustment to the room situation.	Protection class (IP)	IP20
PU1 net weight	0.108	Radial range	Ø 12 m (113 m²)	Ambient temperature	from -25 up to 55 °C
ELECTRICAL		Tangential range	Ø 12 m (113 m²)	Mounting location	ceiling
Mains connection	12 – 22,5 V	Mounting height	2,50 – 3,5 m	Application location	Indoors
Supply voltage detail	DALI bus	Optimal mounting height	2,5 m	Mounting type	Concealed wiring
Switching output 1 potential-free	No	Nevalux sensor technology	DALI 2	Material	Plastic
Switching output 2 potential-free	No	CONNECTIVITY		Application room	function room / ancillary room kitchenette stairwell WC / washroom Indoors
Control output DALI	Addressable/slave	Networking	Yes	Colour	white
Max. current consumption per IEC 62386-101	42 mA	Type of networking	Master/slave	RAL colour	9010
Typical current consumption at 16 V input voltage	8 mA	Networking via	Cable	SCOPE OF DELIVERY & WARRANTY	
Max. current consumption at 10 V input voltage in regular operation	10 mA	Number of DALI participants	5	Manufacturer warranty	5 years
		With bus coupler	Yes	Corner wall bracket included	No
				CERTIFICATES & EPREL	
				Certificates	DALI-2


HF 360 DALI-2 Input Device - concealed

PRESENCE DETECTOR

EAN 4007841057480

Illustrations

TECHNICAL DRAWINGS



56 x 120 x 120 mm

MOUNTING HEIGHT

2,50 – 3,5 m BEREICH	2,5 m OPTIMAL	3,50 m MAX
-------------------------	------------------	---------------


HF 360 DALI-2 Input Device - concealed

EAN 4007841057480

PRESENCE DETECTOR

Wiring Diagrams

WIRING DIAGRAM 1




Circuit diagram

HF 360 DALI-2 Input Device - concealed


EAN 4007841057480

PRESENCE DETECTOR

Highlights



Optional surface-mounting adapter



Optional guard cage



HF ceiling adapter for installation in
suspended ceilings

HF 360 DALI-2 Input Device - concealed

PRESENCE DETECTOR

EAN 4007841057480

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841000363	Aufputz-Adapter Control Pro IP54 weiss	Accessory
 4007841003036	Control PRO Schutzkorb	Accessory

ORDERING INFORMATION

Art.-Nr.

057480

EAN

4007841057480

Typ

HF 360 DALI-2 Input Device - concealed

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss