

IR Quattro HD 24m COM1 - surface white

neva
lux

PRESENCE DETECTOR

EAN 4007841592400

65 x 120 x 120 mm



IR Quattro HD 24m COM1 - surface white

EAN 4007841592400

PRESENCE DETECTOR

Technical Data

IDENTIFICATION		Maximum inrush current		800 A	Time setting		30 s – 30 Min.
PU1 EAN	4007841592400	SENSOR TECHNOLOGY			Base light function		No
Material number	110011875	Max. mounting height		10,00 m	Main light adjustable		No
SAP designation	PRAESENZMELDER IR QUATTRO HD COM1 AP WS	Sensor technology		passive infrared	Functions		Normal / test mode Semi-/fully automatic Pushbutton / switch mode Manual ON / ON-OFF Constant-lighting control ON-OFF
Version	Presence detector	Detection angle		360 °	Settings via		Remote control DIP switches Potentiometers Smart Remote
Product name data sheet	IR Quattro HD 24m COM1 - surface white	Opening angle		160 °	With remote control		No
Product category	Presence detector	Sneak-under protection		Yes	Twilight setting teach		Yes
Discount group	P	Segment-by-segment masking		No	HOUSING & MATERIAL		
Source	Steinel Excel	Electronic scalability		No	Protection class (IP)		IP20
Product status	Normal	Mechanical scalability		Yes	Ambient temperature		from -25 up to 55 °C
Manufacturer	Steinel	Radial range		8 x 8 m (64 m²)	Mounting location		ceiling
DIMENSIONS		Tangential range		20 x 20 m (400 m²)	Application location		Indoors
Dimensions L x W x H	65 x 120 x 120 mm	Detection planes		13	Mounting type		Surface wiring
PU1 net weight	0.242	Switching zones		4800 switching zones	Material		Plastic
ELECTRICAL		Mounting height		2,50 – 10,00 m	Application room		classroom lecture hall open-plan office high-bay warehouse production facilities conference room / meeting room duty room recreation room changing room sports hall reception / lobby multi-storey / underground car park
Mains connection	230 V / 50 – 60 Hz	Presence range		8 x 8 m (64 m²)	Colour		white
Power	2000 W	Optimal mounting height		2,8 m	RAL colour		9010
Fluorescent lamps ECG	1500 W	Nevalux sensor technology		On / Off	SCOPE OF DELIVERY & WARRANTY		
Fluorescent lamps uncompensated	1000 VA	CONNECTIVITY			Manufacturer warranty		5 years
Fluorescent lamps series-compensated	1000 VA	Networking		Yes	Corner wall bracket included		No
Fluorescent lamps parallel-compensated	1000 VA	Type of networking		Master/master Master/slave			
Switching output 1 low-voltage halogen lamps	2000 VA	Networking via		Cable			
LED lamps < 2 W	100 W	LIGHTING TECHNOLOGY					
LED lamps > 2 W < 8 W	300 W	Soft light start		No			
LED lamps > 8 W	600 W	Continuous light		selectable			
Capacitive load in µF	176 µF	Constant light regulation		No			
		SETTINGS					
		Twilight switch		Yes			
		Twilight setting		10 – 1000 lx			


IR Quattro HD 24m COM1 - surface white

PRESENCE DETECTOR

EAN 4007841592400

Illustrations

TECHNICAL DRAWINGS



65 x 120 x 120 mm

MOUNTING HEIGHT


2,50 – 10,00 m BEREICH	2,8 m OPTIMAL	10,00 m MAX
---------------------------	------------------	----------------

IR Quattro HD 24m COM1 - surface white


EAN 4007841592400

PRESENCE DETECTOR

Wiring Diagrams

WIRING DIAGRAM 1

Master circuit diagram

WIRING DIAGRAM 2

Master/master interconnection circuit diagram

IR Quattro HD 24m COM1 - surface white

EAN 4007841592400

PRESENCE DETECTOR


Highlights



4 pyros with DSP (Digital Signal Processing)



Optional remote controls



Optional guard cage

IR Quattro HD 24m COM1 - surface white

PRESENCE DETECTOR

EAN 4007841592400

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841000363	Aufputz-Adapter Control Pro IP54 weiss	Accessory
 4007841003036	Control PRO Schutzkorb	Accessory
 4007841009151	Smart Remote	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory

ORDERING INFORMATION

Art.-Nr.

592400

EAN

4007841592400

Typ

IR Quattro HD 24m COM1 - surface white

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss