

zwena connect HF P450 4K

ZWENA CONNECT P

neva
lux

450 x 82 mm



zwena connect HF P450 4K

ZWENA CONNECT P

Technical Data

IDENTIFICATION

Source	woocommerce
Product status	Normal
Manufacturer	Nevalux

DIMENSIONS

Dimensions Ø x H	450 x 82 mm
Suspension length	1500 mm

ELECTRICAL

Mains connection	200...240 V / 50 – 60 Hz
Power	30 W
Replaceable driver	Yes
Type of wiring	Suitable for through wiring
LED rated current	800 mA

SENSOR TECHNOLOGY

Sensor technology	High frequency
With motion detector	Yes
Detection angle	360°
Radial range	Ø 8 m (50 m²)
Tangential range	Ø 8 m (50 m²)

Mounting height < 4 m

Nevalux sensor technology	Smartlink, BT SIG Mesh
With light sensor	Yes

CONNECTIVITY

With radio network control	Yes
----------------------------	-----

LIGHTING TECHNOLOGY

Colour temperature	4000 K
LED colour deviation	SDCM3
Colour rendering index	80-89
Illuminant	LED
Luminous flux	3100 lm (Down 2100, Up 1000)

Beam angle **Down 95°, Up 100°**

Luminaire luminous efficacy	103 lm/W
-----------------------------	----------

Glare value	UGR < 18
-------------	----------

LIFETIME

LED lifespan (25 °C) 50000 h

SETTINGS

DALI dimming	Yes
--------------	-----

With emergency light	No emergency light
1. The first person to see the accident should call the police and ambulance. 2. If there is a fire, call the fire department. 3. If there is a car accident, call the police. 4. If there is a person who is hurt, call the ambulance. 5. If there is a person who is unconscious, call the ambulance. 6. If there is a person who is bleeding, call the ambulance. 7. If there is a person who is in pain, call the ambulance. 8. If there is a person who is in danger, call the ambulance. 9. If there is a person who is in a dangerous situation, call the ambulance. 10. If there is a person who is in a life-threatening situation, call the ambulance.	1. The first person to see the accident should call the police and ambulance. 2. If there is a fire, call the fire department. 3. If there is a car accident, call the police. 4. If there is a person who is hurt, call the ambulance. 5. If there is a person who is unconscious, call the ambulance. 6. If there is a person who is bleeding, call the ambulance. 7. If there is a person who is in pain, call the ambulance. 8. If there is a person who is in danger, call the ambulance. 9. If there is a person who is in a dangerous situation, call the ambulance. 10. If there is a person who is in a life-threatening situation, call the ambulance.

Direct/indirect ratio	No
separately controllable	

With program-controlled lighting control	Yes
--	-----

Constant light output control	Yes
-------------------------------	-----

HOUSING & MATERIAL

Protection class (IP)	IP20
-----------------------	------

Protection class	I
------------------	---

Ambient temperature -20...45 °C

Housing material	Aluminum
------------------	----------

Cover material	Microprismatic acrylic glass
----------------	------------------------------

Mounting type	Ceiling pendant
1. Recessed 2. Surface 3. Track 4. Flush 5. Surface 6. Flush 7. Surface 8. Flush 9. Surface 10. Flush 11. Surface 12. Flush 13. Surface 14. Flush 15. Surface 16. Flush 17. Surface 18. Flush 19. Surface 20. Flush 21. Surface 22. Flush 23. Surface 24. Flush 25. Surface 26. Flush 27. Surface 28. Flush 29. Surface 30. Flush 31. Surface 32. Flush 33. Surface 34. Flush 35. Surface 36. Flush 37. Surface 38. Flush 39. Surface 40. Flush 41. Surface 42. Flush 43. Surface 44. Flush 45. Surface 46. Flush 47. Surface 48. Flush 49. Surface 50. Flush 51. Surface 52. Flush 53. Surface 54. Flush 55. Surface 56. Flush 57. Surface 58. Flush 59. Surface 60. Flush 61. Surface 62. Flush 63. Surface 64. Flush 65. Surface 66. Flush 67. Surface 68. Flush 69. Surface 70. Flush 71. Surface 72. Flush 73. Surface 74. Flush 75. Surface 76. Flush 77. Surface 78. Flush 79. Surface 80. Flush 81. Surface 82. Flush 83. Surface 84. Flush 85. Surface 86. Flush 87. Surface 88. Flush 89. Surface 90. Flush 91. Surface 92. Flush 93. Surface 94. Flush 95. Surface 96. Flush 97. Surface 98. Flush 99. Surface 100. Flush	1. Recessed 2. Surface 3. Track 4. Flush 5. Surface 6. Flush 7. Surface 8. Flush 9. Surface 10. Flush 11. Surface 12. Flush 13. Surface 14. Flush 15. Surface 16. Flush 17. Surface 18. Flush 19. Surface 20. Flush 21. Surface 22. Flush 23. Surface 24. Flush 25. Surface 26. Flush 27. Surface 28. Flush 29. Surface 30. Flush 31. Surface 32. Flush 33. Surface 34. Flush 35. Surface 36. Flush 37. Surface 38. Flush 39. Surface 40. Flush 41. Surface 42. Flush 43. Surface 44. Flush 45. Surface 46. Flush 47. Surface 48. Flush 49. Surface 50. Flush 51. Surface 52. Flush 53. Surface 54. Flush 55. Surface 56. Flush 57. Surface 58. Flush 59. Surface 60. Flush 61. Surface 62. Flush 63. Surface 64. Flush 65. Surface 66. Flush 67. Surface 68. Flush 69. Surface 70. Flush 71. Surface 72. Flush 73. Surface 74. Flush 75. Surface 76. Flush 77. Surface 78. Flush 79. Surface 80. Flush 81. Surface 82. Flush 83. Surface 84. Flush 85. Surface 86. Flush 87. Surface 88. Flush 89. Surface 90. Flush 91. Surface 92. Flush 93. Surface 94. Flush 95. Surface 96. Flush 97. Surface 98. Flush 99. Surface 100. Flush

Colour White

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
-----------------------	---------

CERTIFICATES & EPREL

EPREL energy efficiency class

zwena connect HF P450 4K

ZWENA CONNECT P

Illustrations


MOUNTING HEIGHT

< 4 m BEREICH
--

zwena connect HF P450 4K

ZWENA CONNECT P

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221753	Emergency Package 1h (50V/1.5W/Compact/PS)	Emergency lighting
 221570	Connect TK2 BLM	Pushbutton interface
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

222054

Typ

zwena connect HF P450 4K

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss