

ayana connect LS C440 TW

AYANA

neva
lux

440 x 95 mm



ayana connect LS C440 TW

AYANA

Technical Data

IDENTIFICATION		CONNECTIVITY			
Source	woocommerce	With radio network control	Yes	Direct/indirect ratio separately controllable	No
Product status	Normal	LIGHTING TECHNOLOGY		With program-controlled lighting control	Yes
Manufacturer	Nevalux	Colour temperature	3000...5600 K	HOUSING & MATERIAL	
DIMENSIONS		LED colour deviation	SDCM3	Protection class (IP)	IP20
Dimensions Ø × H	440 x 95 mm	Colour rendering index	80-89	Protection class	I
ELECTRICAL		Illuminant	LED	Ambient temperature	-20...45 °C
Mains connection	200...240 V / 50 – 60 Hz	Luminous flux	5200 lm (Down 4470, Up 730)	Housing material	Steel
Power	43 W	Beam angle	105°	Cover material	Acrylic glass opal
Replaceable driver	Yes	Luminaire luminous efficacy	122 lm/W	Mounting type	Ceiling / wall surface-mounted
Type of wiring	Suitable for through wiring	Glare value	UGR < 22	Colour	White
SENSOR TECHNOLOGY		LIFETIME		SCOPE OF DELIVERY & WARRANTY	
With motion detector	No	LED lifespan (25 °C)	70000 h	Manufacturer warranty	5 years
Nevalux sensor technology	Smartlink, BT SIG Mesh	SETTINGS		CERTIFICATES & EPREL	
With light sensor	Yes	DALI dimming	Yes	EPREL energy efficiency class	E
		With emergency light	No		

ayana connect LS C440 TW

AYANA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221103	ayana Diffusor 440 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221570	Connect TK2 BLM	Pushbutton interface
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

222006

Typ

ayana connect LS C440 TW

nevalux

AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss