

nefera S V2 Connect CCT

NEFERA CONNECT S

neva
lux

- The new nevalux Connect free-standing luminaires impress with their built-in, networkable lighting control system, which is developed in Switzerland. The control system meets all the requirements of a modern lighting management system. Luminaires can be easily combined into groups. The swarm function ensures comfort in open-plan offices and the cleaning light creates the best conditions for cleaning work. The control system is constantly being further developed and fulfils the demands of modern buildings of the future.

726 x 310 x 1954 mm



nefera S V2 Connect CCT

NEFERA CONNECT S

Technical Data

IDENTIFICATION	
Source	woocommerce
Product status	Normal
Manufacturer	Nevalux
DIMENSIONS	
Dimensions L x W x H	726 x 310 x 1954 mm
ELECTRICAL	
Mains connection	200...240 V / 50 – 60 Hz
Power	80 W
Replaceable driver	Yes
SENSOR TECHNOLOGY	
Sensor technology	passive infrared
With motion detector	Yes
Detection angle	360°
Radial range	4 x 4 m (16 m²)
Tangential range	4 x 4 m (16 m²)
Presence range	4 x 4 m (16 m²)
Nevalux sensor technology	Smartlink, BT SIG Mesh

With light sensor	Yes
CONNECTIVITY	
With radio network control	Yes
LIGHTING TECHNOLOGY	
Colour temperature	3000...5700 K
LED colour deviation	SDCM3
Colour rendering index	80-89
Illuminant	LED
Luminous flux	10400 lm (Down 3850, Up 6550)
Beam angle	Down 80°, Up 115°
Luminaire luminous efficacy	130 lm/W
Glare value	UGR < 18
LIFETIME	
LED lifespan (25 °C)	50000 h
SETTINGS	
DALI dimming	Yes

Direct/indirect ratio separately controllable	No
With program-controlled lighting control	Yes
Constant light output control	Yes
With switch	Yes
HOUSING & MATERIAL	
Protection class (IP)	IP20
Protection class	I
Ambient temperature	-20...45 °C
Housing material	Aluminum
Cover material	Microprismatic acrylic glass
Mounting type	Free standing floor
Colour	White
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
EPREL energy efficiency class	D

nefera S V2 Connect CCT

NEFERA CONNECT S

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221570	Connect TK2 BLM	Pushbutton interface

ORDERING INFORMATION

Art.-Nr.

222043

Typ

nefera S V2 Connect CCT

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss