

elani P2400 4K

ELANI

neva
lux

2400 x 60 x 80 mm



elani P2400 4K

ELANI


Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		Direct/indirect ratio separately controllable	
Source	woocommerce	Colour temperature	4000 K	Yes	
Product status	Normal	LED colour deviation	SDCM3	Yes	
Manufacturer	Nevalux	Colour rendering index	80-89		
DIMENSIONS		Illuminant	Yes, LED-System	HOUSING & MATERIAL	
Dimensions L x W x H	2400 x 60 x 80 mm	Luminous flux	9600 lm (Down 6240, Up 3360)	Protection class (IP)	IP20
Suspension length	2000 mm	Beam angle	Down 105°, Up 115°	Protection class	II
ELECTRICAL		Luminaire luminous efficacy	130 lm/W	Ambient temperature	-20...45 °C
Mains connection	200...240 V / 50 – 60 Hz	Glare value	UGR < 22	Housing material	Aluminium
Power	74 W	LIFETIME		Cover material	Acrylic glass opal
Replaceable driver	Yes	LED lifespan (25 °C)	70000 h	Mounting type	Ceiling pendant
Type of wiring	Suitable for through wiring	SETTINGS		Colour	Aluminium
SENSOR TECHNOLOGY		DALI dimming	Yes	SCOPE OF DELIVERY & WARRANTY	
With motion detector	No	With emergency light	No	Manufacturer warranty	5 years
Nevalux sensor technology	DALI 2	Suitable for light band configuration	Yes	CERTIFICATES & EPREL	
With light sensor	No			EPREL energy efficiency class	D

elani P2400 4K

ELANI

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221101	elani Diffusor 2500 CDP	
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221343	elani Connector 90°	Coupler/connector L-shape
 221107	elani Link	Coupler/connector straight
 221396	elani Color RAL_NCS_2400	Other
 221996	elani WM-Set 2B	Mounting kit

ORDERING INFORMATION

Art.-Nr.

221117

Typ

elani P2400 4K

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss