

Dual HF DALI-2 APC - Unterputz

DUAL HF

neva
lux

74 x 120 x 120 mm



Dual HF DALI-2 APC - Unterputz

DUAL HF

Technical Data

IDENTIFICATION		Mechanical scalability		Settings via		Remote control\nDIP switches\nPotentiometers\nSmart Remote	
Version	Presence detector	Radial range	20 x 3 m (60 m²)	With remote control			No
Source	woocommerce	Tangential range	20 x 3 m (60 m²)	Twilight setting teach			Yes
Product status	Normal	Mounting height	2,50 – 3,50 m	Base light function in percent			10 %
Manufacturer	Nevalux	Optimal mounting height	2,8 m	Base light function percent from			10
DIMENSIONS		Nevalux sensor technology		HOUSING & MATERIAL			
Dimensions L x W x H	74 x 120 x 120 mm	CONNECTIVITY		Protection class (IP)			IP20
ELECTRICAL		Networking	Yes	Ambient temperature			-25 – 55 °C
Mains connection	230 V / 50 – 60 Hz	Type of networking	Master/slave	Mounting location			ceiling
Control output DALI	Broadcast 2x12 electronic ballasts	Networking via	Cable	Application location			Indoors
SENSOR TECHNOLOGY		LIGHTING TECHNOLOGY		Mounting type			Concealed wiring
Max. mounting height	3,50 m	Soft light start	Yes	Material			Plastic
Sensor technology	High frequency	Constant light regulation	Yes	Application room			corridor / aisle\nIndoors
		SETTINGS		Colour			white
Transmission power	< 1 mW	Twilight switch	Yes	RAL colour			9010
HF technology	5,8 GHz	Twilight setting	10 – 1000 lx	SCOPE OF DELIVERY & WARRANTY			
Detection	also through glass, wood and stud walls	Time setting	30 s – 30 Min.	Manufacturer warranty			5 years
Detection angle	360 °	Base light function	Yes	Corner wall bracket included			No
Opening angle	140 °	Base light function time	1-60 min, all night	CERTIFICATES & EPREL			
Sneak-under protection	Yes	Functions	Normal / test mode\nSemi-/fully automatic\nPushbutton / switch mode\nManual ON / ON-OFF\nConstant-lighting control ON-OFF	Certificates			DALI-2
Segment-by-segment masking	No						
Electronic scalability	Yes						

Dual HF DALI-2 APC - Unterputz

DUAL HF

Illustrations

MOUNTING HEIGHT

2,50 – 3,50 m BEREICH	2,8 m OPTIMAL	3,50 m MAX
--------------------------	------------------	---------------

Dual HF DALI-2 APC - Unterputz

DUAL HF

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841006600	HF-Deckenadapter	Accessory
 4007841592806	Nutzer Fernbedienung RC5	Accessory
 4007841000363	Aufputz-Adapter Control Pro IP54 weiss	Accessory
 4007841003036	Control PRO Schutzkorb	Accessory
 4007841009151	Smart Remote	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841003005

Typ

Dual HF DALI-2 APC - Unterputz

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss