

ayana DALI P570 3K

AYANA

neva
lux

- Timeless simple acrylic glass luminaire in 3 different sizes
- Available in ceiling and pendant versions
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- Connect version available with light sensor (LS) or with motion detector and light sensor (PIR)
- For universal use for illumination of offices, schools, traffic zones, etc.
- Very high quality workmanship from Swiss manufacturing
- Sophisticated thermal management for long service life
- Variants with adjustable light color (Tunable White) to emulate the natural course of daylight

570 x 95 mm



ayana DALI P570 3K

AYANA

Technical Data

IDENTIFICATION		With light sensor		No	With emergency light		No
Source	woocommerce	LIGHTING TECHNOLOGY					
Product status	Normal	Colour temperature	3000 K				
Manufacturer	Nevalux	LED colour deviation	SDCM3				
DIMENSIONS		Colour rendering index	80-89				
Dimensions Ø × H	570 x 95 mm	Illuminant	LED				
Suspension length	2000 mm	Luminous flux	6100 lm (Down 5250, Up 850)				
ELECTRICAL		Beam angle	105°				
Mains connection	200...240 V / 50 – 60 Hz	Luminaire luminous efficacy	120 lm/W				
Power	51 W	Glare value	UGR < 21				
Replaceable driver	Yes	LIFETIME					
Type of wiring	Suitable for through wiring	LED lifespan (25 °C)	70000 h				
SENSOR TECHNOLOGY		SETTINGS					
With motion detector	No	DALI dimming	Yes				
Nevalux sensor technology	DALI 2, On / Off						

HOUSING & MATERIAL	
Protection class (IP)	IP20
Protection class	I
Ambient temperature	-20...45 °C
Housing material	Steel
Cover material	Acrylic glass opal
Mounting type	Ceiling pendant
Colour	White
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
EPREL energy efficiency class	E

ayana DALI P570 3K

AYANA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221104	ayana Diffusor 570 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.

221151

Typ

ayana DALI P570 3K

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss