

iFux CityStreet4 60W DN10 3K

IFUX CITYSTREET 4

neva
lux

- The iFux CityStreet 4 luminaire is an intelligent and functional street light of the latest generation. It convinces by very good corrosion protection and best maintenance characteristics. Variable candelabra diameters ensure universal use.

458 x 240 x 100 mm



iFux CityStreet4 60W DN10 3K

IFUX CITYSTREET 4

Technical Data

IDENTIFICATION

Variant	Narrow beam DN10, 60W
Source	woocommerce
Product status	Normal
Manufacturer	Nevalux

DIMENSIONS

Dimensions L x W x H	458 x 240 x 100 mm
Suitable for pole-top diameter	48...76 mm

ELECTRICAL

Mains connection	90...264 VAC / 47 – 63 Hz
Power	60 W
Power factor	0.92

SENSOR TECHNOLOGY

With motion detector	No
Nevalux sensor technology	E-Save

With light sensor	No
-------------------	----

CONNECTIVITY

With radio network control	No
----------------------------	----

LIGHTING TECHNOLOGY

Colour temperature	3000...3000 K
Colour rendering index	70-79
Luminous flux	8520 lm
Beam angle	Narrow
Luminaire luminous efficacy	142 lm/W

LIFETIME

LED lifespan (25 °C)	100000 h
----------------------	----------

SETTINGS

DALI dimming	Yes
With program-controlled lighting control	No

HOUSING & MATERIAL

Impact resistance	IK09
Protection class (IP)	IP66
Protection class	II
Ambient temperature	-30...55 °C
Housing material	Aluminium
Cover material	Clear glass
Mounting type	Column Post-top/side-entry
Colour	Anthracite

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
With connection cable	Yes

CERTIFICATES & EPREL

EPREL energy efficiency class	A++, A+, A (LED)
-------------------------------	------------------

iFux CityStreet4 60W DN10 3K

IFUX CITYSTREET 4

Accessories

ORDERING INFORMATION	
Art.-Nr.	221188
Typ	iFux CityStreet4 60W DN10 3K
neva lux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	