

fayola 125 V2 3CCT DALI

SERIE FAYOLA V2

neva
lux

145 x 45 mm



fayola 125 V2 3CCT DALI

SERIE FAYOLA V2

Technical Data

IDENTIFICATION		SENSOR TECHNOLOGY		SETTINGS	
Source	woocommerce	With motion detector	No	DALI dimming	Yes
Product status	Normal	Nevalux sensor technology	DALI 2	HOUSING & MATERIAL	
Manufacturer	Nevalux	LIGHTING TECHNOLOGY		Protection class (IP)	IP44
DIMENSIONS		Colour temperature	2700 / 4000 / 5700 K	Protection class	II
Dimensions Ø × H	145 x 45 mm	LED colour deviation	SDCM3	Ambient temperature	-20...45 °C
Drill hole	125 mm	Colour rendering index	80-89	Housing material	Aluminum
ELECTRICAL		Illuminant	LED	Cover material	Microprismatic acrylic glass
Mains connection	220...240 V / 50 – 60 Hz	Luminous flux	1450 lm	Mounting type	In-ceiling installation
Power	18 W	Beam angle	90°	Colour	White
Replaceable driver	Yes	Luminaire luminous efficacy	81 lm/W	SCOPE OF DELIVERY & WARRANTY	
Type of wiring	Ending	Glare value	UGR<27	Manufacturer warranty	5 years
LED rated current	450 mA	LIFETIME		CERTIFICATES & EPREL	
		LED lifespan (25 °C)	50000 h	EPREL energy efficiency class	F

fayola 125 V2 3CCT DALI

SERIE FAYOLA V2

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221446	fayola 100 V2 3CCT DALI	
 221448	fayola 150 V2 3CCT DALI	
 221449	fayola 175 V2 3CCT DALI	
 221450	fayola 205 V2 3CCT DALI	
 220721	Emergency Package 1h (50V/2.5W/Box)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.

221447

Typ

fayola 125 V2 3CCT DALI

nevalux

AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss