

fayola MF1 IP65 DALI D2W

FAYOLA MF1 IP65

neva
lux

90 x 56 mm



fayola MF1 IP65 DALI D2W

FAYOLA MF1 IP65

Technical Data

IDENTIFICATION	
Source	woocommerce
Product status	Normal
Manufacturer	Nevalux
DIMENSIONS	
Dimensions Ø × H	90 x 56 mm
Drill hole	75 mm
ELECTRICAL	
Mains connection	220...240 V / 50 – 60 Hz
Power	8 W
Replaceable driver	Yes
Type of wiring	Ending
LED rated current	350 mA
SENSOR TECHNOLOGY	
With motion detector	No
Nevalux sensor technology	DALI 2
LIGHTING TECHNOLOGY	
Colour temperature	1800...3000 K
LED colour deviation	SDCM3
Colour rendering index	80-89
Illuminant	LED
Luminous flux	470 lm
Beam angle	60°
Luminaire luminous efficacy	59 lm/W
LIFETIME	
LED lifespan (25 °C)	50000 h
SETTINGS	
DALI dimming	Yes
HOUSING & MATERIAL	
Protection class (IP)	IP65
Protection class	II
Ambient temperature	-20...40 °C
Housing material	Aluminum
Cover material	Reflector aluminium
Mounting type	In-ceiling installation
Colour	White
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
EPREL energy efficiency class	G

fayola MF1 IP65 DALI D2W

FAYOLA MF1 IP65

Accessories

ORDERING INFORMATION

Art.-Nr. 220448

Typ **fayola MF1 IP65 DALI D2W**

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss