

ayana connect LS P850 3K

AYANA

neva
lux

850 x 95 mm



ayana connect LS P850 3K

AYANA

Technical Data

IDENTIFICATION		CONNECTIVITY		Direct/indirect ratio separately controllable	No
Source	woocommerce	With radio network control	Yes	With program-controlled lighting control	Yes
Product status	Normal	LIGHTING TECHNOLOGY		Constant light output control	Yes
Manufacturer	Nevalux	Colour temperature	3000 K	HOUSING & MATERIAL	
DIMENSIONS		LED colour deviation	SDCM3	Protection class (IP)	IP20
Dimensions Ø × H	850 x 95 mm	Colour rendering index	80-89	Protection class	I
Suspension length	2000 mm	Illuminant	LED	Ambient temperature	-20...45 °C
ELECTRICAL		Luminous flux	9800 lm (Down 8430, Up 1370)	Housing material	Steel
Mains connection	200...240 V / 50 – 60 Hz	Beam angle	105°	Cover material	Acrylic glass opal
Power	78 W	Luminaire luminous efficacy	126 lm/W	Mounting type	Ceiling pendant
Replaceable driver	Yes	Glare value	UGR < 21	Colour	White
Type of wiring	Suitable for through wiring	LIFETIME		SCOPE OF DELIVERY & WARRANTY	
SENSOR TECHNOLOGY		LED lifespan (25 °C)	70000 h	Manufacturer warranty	5 years
With motion detector	No	SETTINGS		CERTIFICATES & EPREL	
Nevalux sensor technology	Smartlink, BT SIG Mesh	DALI dimming	Yes	EPREL energy efficiency class	D
With light sensor	Yes	With emergency light	No		

ayana connect LS P850 3K

AYANA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221105	ayana Diffusor 850 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221366	Connect RTC	Real-time clock
 221570	Connect TK2 BLM	Pushbutton interface
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

222029

Typ

ayana connect LS P850 3K

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss