

ayana connect LS P850 4K

AYANA

neva
lux

850 x 95 mm



ayana connect LS P850 4K

AYANA

Technical Data

IDENTIFICATION		CONNECTIVITY		Direct/indirect ratio separately controllable	No
Source	woocommerce	With radio network control	Yes	With program-controlled lighting control	Yes
DIMENSIONS		LIGHTING TECHNOLOGY		Constant light output control	Yes
Dimensions Ø × H	850 x 95 mm	Colour temperature	4000 K	HOUSING & MATERIAL	
Suspension length	2000 mm	LED colour deviation	SDCM3	Protection class (IP)	IP20
ELECTRICAL		Colour rendering index	80-89	Protection class	I
Mains connection	200...240 V / 50 – 60 Hz	Illuminant	LED	Ambient temperature	-20...45 °C
Power	78 W	Luminous flux	9800 lm (Down 8430, Up 1370)	Housing material	Steel
Replaceable driver	Yes	Beam angle	105°	Cover material	Acrylic glass opal
Type of wiring	Suitable for through wiring	Luminaire luminous efficacy	126 lm/W	Mounting type	Ceiling pendant
SENSOR TECHNOLOGY		Glare value	UGR < 21	Colour	White
With motion detector	No	LIFETIME		SCOPE OF DELIVERY & WARRANTY	
Nevalux sensor technology	Smartlink, BT SIG Mesh	LED lifespan (25 °C)	70000 h	Manufacturer warranty	5 years
With light sensor	Yes	SETTINGS		CERTIFICATES & EPREL	
		DALI dimming	Yes	EPREL energy efficiency class	D
		With emergency light	No		

ayana connect LS P850 4K

AYANA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221105	ayana Diffusor 850 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221366	Connect RTC	Real-time clock
 221570	Connect TK2 BLM	Pushbutton interface
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

222028

Typ

ayana connect LS P850 4K

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss