

iFux City Park Pole Connect 53W 3K Master GPS

neva
lux

IFUX CITY PARK POLE CONNECT

- The iFux City Park Pole luminaire is a timeless street light of the latest generation. It has an adjustable brightness for the main and orientation light as well as a built-in motion detector. Thanks to the integrated radio communication, an intelligent network with several lights can be easily set up. In conjunction with the neighbor function, the light precedes the user. Old luminaires can be replaced without rewiring. Variable candelabra diameters ensure universal use.

550 x 550 mm



iFux City Park Pole Connect 53W 3K Master GPS

IFUX CITY PARK POLE CONNECT

Technical Data

IDENTIFICATION			
Variant	Wide beam	Tangential range	10 m
Source	woocommerce	Nevalux sensor technology	E-Save
Product status	Normal	With light sensor	Yes
Manufacturer	Nevalux	CONNECTIVITY	
DIMENSIONS		With radio network control	Yes
Dimensions L x W x H	550 x 550 mm	LIGHTING TECHNOLOGY	
Suitable for pole-top diameter	48...76 mm	Colour temperature	3000...3000 K
ELECTRICAL		Colour rendering index	70-79
Mains connection	90...264 VAC / 47 – 63 Hz	Luminous flux	7526 lm
Power	53 W	Beam angle	Medium
Power factor	0.92	Luminaire luminous efficacy	142 lm/W
SENSOR TECHNOLOGY		LIFETIME	
Sensor technology	passive infrared	LED lifespan (25 °C)	100000 h
With motion detector	Yes	SETTINGS	
Detection angle	100°	DALI dimming	Yes
		With program-controlled lighting control	Yes, incl. GPS
		HOUSING & MATERIAL	
		Impact resistance	IK10
		Protection class (IP)	IP66
		Protection class	II
		Ambient temperature	-30...55 °C
		Housing material	Aluminium
		Cover material	Clear glass
		Mounting type	Column Post-top
		Colour	Anthracite
		SCOPE OF DELIVERY & WARRANTY	
		Manufacturer warranty	5 years
		With connection cable	Yes
		CERTIFICATES & EPREL	
		EPREL energy efficiency class	A++, A+, A (LED)

iFux City Park Pole Connect 53W 3K Master GPS

IFUX CITY PARK POLE CONNECT

Accessories

ORDERING INFORMATION	
Art.-Nr.	221467
Typ	iFux City Park Pole Connect 53W 3K Master GPS
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	