

fayola M6 On-Off/Phasecut D2W

FAYOLA M6

neva
lux

50 x 48 mm



fayola M6 On-Off/Phasecut D2W

FAYOLA M6

Technical Data

IDENTIFICATION		SENSOR TECHNOLOGY		SETTINGS	
Source	woocommerce	With motion detector	No	DALI dimming	No
Product status	Normal	Nevalux sensor technology	On / Off	HOUSING & MATERIAL	
Manufacturer	Nevalux	LIGHTING TECHNOLOGY		Protection class (IP)	IP20
DIMENSIONS		Colour temperature	1800...3000 K	Protection class	II
Dimensions Ø × H	50 x 48 mm	LED colour deviation	SDCM3	Ambient temperature	-20...40 °C
Drill hole	60 mm	Colour rendering index	80-89	Housing material	Aluminum
ELECTRICAL		Illuminant	LED	Cover material	Reflector aluminium
Mains connection	220...240 V / 50 – 60 Hz	Luminous flux	470 lm	Mounting type	In-ceiling installation
Power	8 W	Beam angle	60°	Colour	Aluminum
Replaceable driver	Yes	Luminaire luminous efficacy	59 lm/W	SCOPE OF DELIVERY & WARRANTY	
Type of wiring	Ending	LIFETIME		Manufacturer warranty	5 years
LED rated current	350 mA	LED lifespan (25 °C)	50000 h	CERTIFICATES & EPREL	
				EPREL energy efficiency class	G

fayola M6 On-Off/Phasecut D2W

FAYOLA M6

Accessories

ORDERING INFORMATION

Art.-Nr. 220281

Typ **fayola M6 On-Off/Phasecut D2W**

**neva
lux**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss