

RS PRO P1 FLAT SP warmweiss

P-SERIE FLAT

neva
lux

272 x 64 mm



RS PRO P1 FLAT SP warmweiss

P-SERIE FLAT

Technical Data

IDENTIFICATION

Source	woocommerce
Product status	Normal
Manufacturer	Nevalux

DIMENSIONS

Dimensions Ø x H	272 x 64 mm
------------------	-------------

ELECTRICAL

Mains connection	220 – 240 V / 50 – 60 Hz
Power	8,2 W

SENSOR TECHNOLOGY

With motion detector	No
----------------------	----

CONNECTIVITY

Networking via	Cable
----------------	-------

LIGHTING TECHNOLOGY

Measured luminous flux 360°	922 lm
Colour temperature	3000 K
Illuminant	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
Soft light start	Yes

LIFETIME

LED lifetime max. °C	60000 h
LED lifetime L70B50 25°C	> 60000 h
Luminous flux decline per LM80	L80B10

SETTINGS

Main light adjustable	No
-----------------------	----

HOUSING & MATERIAL

Impact resistance	IK03
Protection class (IP)	IP54
Protection class	II
Ambient temperature	from -10 up to 40 °C
Housing material	Plastic
Cover material	Plastic, opal
Mounting location	ceiling
Application location	Indoors
Colour	white

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
-----------------------	---------

CERTIFICATES & EPREL

Certificates	DEKRA
--------------	-------

RS PRO P1 FLAT SP warmweiss

P-SERIE FLAT

Accessories

ORDERING INFORMATION	
Art.-Nr.	221820
Typ	RS PRO P1 FLAT SP warmweiss
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	