

# lisha V2 connect LS P1500 4K

LISHA V2

**neva**  
**lux**

Product code **221624**

- For universal use for illumination of offices, schools, traffic zones, etc.
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- Connect version available with light sensor (LS) or with motion detector and light sensor (PIR)
- Microprismatic diffuser for best possible glare control
- Link technology for seamless extension of the luminaire with continuous wiring
- Variants with 1.2 and 1.5 meter length available
- Housing Aluminium white



lisha V2 connect LS P1500 4K

LISHA V2

Product code 221624

Technical Data

| DIMENSIONS                                       |                                                                                | LIGHTING TECHNOLOGY                   |                              |                                               |                              |
|--------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------|------------------------------|-----------------------------------------------|------------------------------|
| Dimensions L x W x H                             | 1518 x 60 x 80 mm                                                              | Colour temperature                    | 4000 K                       | Direct/indirect ratio separately controllable | No                           |
| Suspension length                                | 1500 mm                                                                        | LED colour deviation                  | SDCM3                        | With program-controlled lighting control      | Yes                          |
| ELECTRICAL                                       |                                                                                | Colour rendering index                | 80-89                        | Constant light output control                 | Yes                          |
| Mains connection                                 | 200...240 V / 50 – 60 Hz                                                       | Illuminant                            | LED                          | HOUSING & MATERIAL                            |                              |
| Power                                            | 60 W                                                                           | Luminous flux                         | 7800 lm (Down 2340, Up 5460) | Protection class (IP)                         | IP20                         |
| Replaceable driver                               | Yes                                                                            | Beam angle                            | Down 90°, Up 110°            | Protection class                              | I                            |
| Type of wiring                                   | Through wiring included                                                        | Luminaire luminous efficacy           | 130 lm/W                     | Ambient temperature                           | -20...45 °C                  |
| LED rated current                                | 1500 mA                                                                        | Glare value                           | UGR < 19                     | Housing material                              | Aluminum                     |
| Maximum number of luminaires per circuit breaker | C10: 18x, C13: 23x, C16: 28x, C20: 35x, B10: 15x, B13: 20x, B16: 24x, B20: 30x | LIFETIME                              |                              | Cover material                                | Microprismatic acrylic glass |
|                                                  |                                                                                | LED lifespan (25 °C)                  | 50000 h                      | Mounting type                                 | Ceiling pendant              |
| SENSOR TECHNOLOGY                                |                                                                                | SETTINGS                              |                              | Colour                                        | white                        |
| With motion detector                             | No                                                                             | DALI dimming                          | Yes                          | SCOPE OF DELIVERY & WARRANTY                  |                              |
| With light sensor                                | Yes                                                                            | With emergency light                  | No                           | Manufacturer warranty                         | 5 years                      |
| CONNECTIVITY                                     |                                                                                | Suitable for light band configuration | Yes                          | CERTIFICATES & EPREL                          |                              |
| With radio network control                       | Yes                                                                            |                                       |                              | EPREL energy efficiency class                 | D                            |

lisha V2 connect LS P1500 4K

Product code 221624

LISHA V2

Accessories

| ARTICLE NUMBER                                                                            | DESCRIPTION                                 | CATEGORY                   |
|-------------------------------------------------------------------------------------------|---------------------------------------------|----------------------------|
|  221642   | lisha V2 Diffusor 1M                        | Cover                      |
|  221643   | lisha V2 Link P                             | Coupler/connector straight |
|  221644   | lisha V2 CBox Connect                       | Adapter                    |
|  221618  | Emergency Package 1h (50V/3.5W)             | Emergency lighting         |
|  221570 | Connect TK2 BLM                             | Pushbutton interface       |
|  221591 | Smartlink T-Board PB4                       | Wireless push-button       |
|  221970 | Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2 | Wireless push-button       |
|  221971 | Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4 | Wireless push-button       |

ORDERING INFORMATION

Art.-Nr.

221624

Typ

lisha V2 connect LS P1500 4K

nevalux

nevalux AG  
Neugrütstrasse 2  
8610 Uster  
+41 44 508 78 78  
info@nevalux.swiss