

nayo P Diffused 4K

NAYO P DIFFUSED 4K

neva
lux

1190 x 160 x 30 mm



nayo P Diffused 4K

NAYO P DIFFUSED 4K

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		Direct/indirect ratio separately controllable	
Source	woocommerce	Colour temperature	4000 K		No
Product status	Normal	LED colour deviation	SDCM3	Constant light output control	Yes
Manufacturer	Nevalux	Colour rendering index	80-89	HOUSING & MATERIAL	
DIMENSIONS		Illuminant	LED	Protection class (IP)	IP20
Dimensions L x W x H	1190 x 160 x 30 mm	Luminous flux	7200 lm (Down 3600, Up 3600)	Protection class	I
Suspension length	1500 mm	Beam angle	Down 105°, Up 115°	Ambient temperature	-20...45 °C
ELECTRICAL		Luminaire luminous efficacy	120 lm/W	Housing material	Aluminum
Mains connection	200...240 V / 50 – 60 Hz	Glare value	UGR < 19	Cover material	Microprismatic acrylic glass
Power	60 W	LIFETIME		Mounting type	Ceiling pendant
Replaceable driver	Yes	LED lifespan (25 °C)	50000 h	Colour	White
Type of wiring	Through wiring included	SETTINGS		SCOPE OF DELIVERY & WARRANTY	
SENSOR TECHNOLOGY		DALI dimming	Yes	Manufacturer warranty	5 years
With motion detector	No	With emergency light	No	CERTIFICATES & EPREL	
Nevalux sensor technology	DALI 2	Suitable for light band configuration	Yes	EPREL energy efficiency class	E
With light sensor	No				

nayo P Diffused 4K

NAYO P DIFFUSED 4K

Accessories

ORDERING INFORMATION	
Art.-Nr.	220463
Typ	nayo P Diffused 4K
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	