

zwena DALI P350 3K

ZWENA CONNECT P

neva
lux

- For universal use for illumination of offices, schools, traffic zones, etc.
- Optionally as an intelligent Connect version with or without motion sensor, or as a conventional DALI luminaire
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- High quality finish
- Direct and indirect light distribution

350 x 82 mm



zwena DALI P350 3K

ZWENA CONNECT P

Technical Data

IDENTIFICATION		With light sensor		No	With emergency light		No	
Source	woocommerce	LIGHTING TECHNOLOGY						No
Product status	Normal	Colour temperature		3000 K		Direct/indirect ratio separately controllable		
Manufacturer	Nevalux	LED colour deviation		SDCM3		HOUSING & MATERIAL		
DIMENSIONS		Colour rendering index		80-89		Protection class (IP)		IP20
Dimensions Ø × H	350 x 82 mm	Illuminant		LED		Protection class		I
Suspension length	1500 mm	Luminous flux		1700 lm (Down 1200, Up 500)		Ambient temperature		-20...45 °C
ELECTRICAL		Beam angle		Down 95°, Up 100°		Housing material		Aluminum
Mains connection	200...240 V / 50 – 60 Hz	Luminaire luminous efficacy		94 lm/W		Cover material		Microprismatic acrylic glass
Power	18 W	Glare value		UGR < 18		Mounting type		Ceiling pendant
Replaceable driver	Yes	LIFETIME						White
Type of wiring	Suitable for through wiring	SETTINGS						SCOPE OF DELIVERY & WARRANTY
LED rated current	450 mA	DALI lifespan (25 °C)		50000 h		Manufacturer warranty		5 years
SENSOR TECHNOLOGY		CERTIFICATES & EPREL						
With motion detector	No	DALI dimming		Yes		EPREL energy efficiency class		F
Nevalux sensor technology	DALI 2							

zwena DALI P350 3K

ZWENA CONNECT P

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220579	zwena DALI P450 3K	
 220581	zwena DALI P600 3K	
 220583	zwena DALI P900 3K	
 220692	Emergency Package 1h (50V/1.5W/Compact)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.

220577

Typ

zwena DALI P350 3K

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss