

IS 3360 MX Highbay PF - surface, sq.

MOTION DETECTOR

neva
lux

EAN 4007841033583

65 x 95 x 95 mm



IS 3360 MX Highbay PF - surface, sq.

MOTION DETECTOR

EAN 4007841033583

Technical Data

IDENTIFICATION					
PU1 EAN	4007841033583	Capacitive load in µF	176 µF	Twilight setting	2 – 1000 lx
Material number	110046035	Maximum inrush current	110 A	Time setting	5 s – 15 Min.
SAP designation	BEWEGUNGSMELDER IS 3360 MX-E PF AP WS	SENSOR TECHNOLOGY		Base light function	No
Version	Motion detectors	Max. mounting height	14,00 m	Main light adjustable	No
Product name data sheet	IS 3360 MX Highbay PF - surface, sq.	Sensor technology	passive infrared	Functions	Normal / test mode Manual ON / ON-OFF
Product category	Motion detector	With motion detector	Yes	Settings via	Remote control Potentiometers Smart Remote
Discount group	B	Detection angle	360 °	With remote control	No
Source	Steinel Excel	Opening angle	180 °	Twilight setting teach	Yes
Product status	Normal	Sneak-under protection	Yes	HOUSING & MATERIAL	
Manufacturer	Steinel	Segment-by-segment masking	Yes	Protection class (IP)	IP54
DIMENSIONS		Electronic scalability	No	Ambient temperature	from -20 up to 50 °C
Dimensions L × W × H	65 x 95 x 95 mm	Mechanical scalability	No	Housing material	Plastic
PU1 net weight	0.179	Radial range	Ø 14 m (154 m²)	Cover material	Plastic, opal
ELECTRICAL		Tangential range	Ø 36 m (1018 m²)	Cover material (scope of delivery)	shrouds
Mains connection	220 – 240 V / 50 – 60 Hz	Switching zones	1416 switching zones	Mounting location	ceiling
Power	2000 W	Mounting height	4,00 – 14,00 m	Application location	Indoors
Fluorescent lamps ECG	1500 W	Optimal mounting height	12 m	Mounting type	Surface wiring
Fluorescent lamps uncompensated	1000 VA	CONNECTIVITY		Material	Plastic
Fluorescent lamps series-compensated	400 VA	Networking	Yes	Application room	high-bay warehouse sports hall Indoors
Fluorescent lamps parallel-compensated	400 VA	Type of networking	Master/master	Colour	white
Switching output 1 low-voltage halogen lamps	2000 VA	Networking via	Cable	RAL colour	9003
LED lamps < 2 W	100 W	LIGHTING TECHNOLOGY		SCOPE OF DELIVERY & WARRANTY	
LED lamps > 2 W < 8 W	300 W	Soft light start	No	Manufacturer warranty	5 years
LED lamps > 8 W	600 W	Continuous light	selectable, 4h	Corner wall bracket included	No
		Constant light regulation	No		
		SETTINGS			
		Twilight switch	Yes		


IS 3360 MX Highbay PF - surface, sq.

MOTION DETECTOR

EAN 4007841033583

Illustrations

TECHNICAL DRAWINGS



65 x 95 x 95 mm

MOUNTING HEIGHT

4,00 – 14,00 m BEREICH	12 m OPTIMAL	14,00 m MAX
---------------------------	-----------------	----------------


IS 3360 MX Highbay PF - surface, sq.

MOTION DETECTOR

EAN 4007841033583

Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

IS 3360 MX Highbay PF - surface, sq.


EAN 4007841033583

MOTION DETECTOR

Highlights



UV-resistant plastic



Large terminal compartment



Optional remote controls

IS 3360 MX Highbay PF - surface, sq.

MOTION DETECTOR

EAN 4007841033583

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841009151	Smart Remote	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory
 4007841056711	Schwarze Blende für IR-Sensoren Aufputz eckig	Accessory
 4007841056735	Schwarze Blende für IR-Sensoren Aufputz rund	Accessory

ORDERING INFORMATION

Art.-Nr.

033583

EAN

4007841033583

Typ

IS 3360 MX Highbay PF - surface, sq.

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss