

nefera S 4K

NEFERA CONNECT S

neva
lux

- Version: Master

610 x 310 x 1950 mm



nefera S 4K

NEFERA CONNECT S

Technical Data

IDENTIFICATION		With light sensor		Yes	SETTINGS	
Source	woocommerce	LIGHTING TECHNOLOGY			Direct/indirect ratio separately controllable	No
Product status	Normal	Colour temperature	4000...4000 K		With switch	Yes
Successor	221987	LED colour deviation	SDCM3		HOUSING & MATERIAL	
Manufacturer	Nevalux	Colour rendering index	80-89		Protection class (IP)	IP20
DIMENSIONS		Illuminant	LED		Protection class	II
Dimensions L x W x H	610 x 310 x 1950 mm	Luminous flux	8000 lm (Down 4000, Up 4000)		Ambient temperature	-20...45 °C
ELECTRICAL		Beam angle	Down 90°, Up 110°		Housing material	Aluminium
Mains connection	200...240 V / 50 – 60 Hz	Luminaire luminous efficacy	100 lm/W		Cover material	Microprismatic acrylic glass
Power	80 W	Glare value	UGR < 19		Colour	white
SENSOR TECHNOLOGY		LIFETIME			SCOPE OF DELIVERY & WARRANTY	
With motion detector	Yes	LED lifespan (25 °C)	50000 h		Manufacturer warranty	5 years

nefera S 4K

NEFERA CONNECT S

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220173	nefera C120 4K	
 220172	nefera C60 4K	
 220171	nefera P 4K	
 220560	nefera W60 4K	

ORDERING INFORMATION

Art.-Nr.

220170

Typ

nefera S 4K

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss