

aluna connect PIR P630 4K

ALUNA

neva
lux

- Timeless simple textile lamp in 3 different sizes
- Available in ceiling and pendant versions
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- Connect version available with light sensor (LS) or with motion detector and light sensor (PIR)
- For universal use for illumination of offices, schools, traffic zones, etc.
- Very high quality workmanship from Swiss manufacturing
- Sophisticated thermal management for long service life
- Variants with adjustable light color (Tunable White) to emulate the natural course of daylight
- Fabric shade can be ordered in any color

630 x 118 mm



aluna connect PIR P630 4K

ALUNA

Technical Data

IDENTIFICATION		Nevalux sensor technology		Smartlink, BT SIG Mesh	With emergency light		No
Source	woocommerce	With light sensor		Yes	Direct/indirect ratio separately controllable		No
Product status	Normal	CONNECTIVITY			With program-controlled lighting control		Yes
Manufacturer	Nevalux	With radio network control		Yes	Constant light output control		Yes
DIMENSIONS		LIGHTING TECHNOLOGY			HOUSING & MATERIAL		
Dimensions Ø × H	630 x 118 mm	Colour temperature		4000 K	Protection class (IP)		IP20
Suspension length	2000 mm	LED colour deviation		SDCM3	Protection class		I
ELECTRICAL		Colour rendering index		80-89	Ambient temperature		-20...45 °C
Mains connection	200...240 V / 50 – 60 Hz	Illuminant		LED	Housing material		Steel
Power	51 W	Luminous flux		6100 lm (Down 5250, Up 850)	Cover material		Acrylic glass opal
Replaceable driver	Yes	Beam angle		105°	Mounting type		Ceiling pendant
Type of wiring	Suitable for through wiring	Luminaire luminous efficacy		120 lm/W	Colour		White
SENSOR TECHNOLOGY		Glare value		UGR < 21	SCOPE OF DELIVERY & WARRANTY		
Sensor technology	passive infrared	LIFETIME			Manufacturer warranty		5 years
With motion detector	Yes	LED lifespan (25 °C)		70000 h	CERTIFICATES & EPREL		
Detection angle	360°	SETTINGS			EPREL energy efficiency class		E
Radial range	4 x 4 m (16 m²)	DALI dimming		Yes			
Tangential range	6 x 6 m (36 m²)						
Presence range	4 x 4 m (16 m²)						

aluna connect PIR P630 4K

ALUNA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221104	ayana Diffusor 570 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221366	Connect RTC	Real-time clock
 221570	Connect TK2 BLM	Pushbutton interface
 221845	aluna Color RAL_NCS_0630	Other
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

221424

Typ

aluna connect PIR P630 4K

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss