

elani connect P3200 3K

ELANI

neva
lux

Product code **221111**

- Built-in, networkable light management for next generation lighting projects
- up to 70% energy savings compared to a conventional solution thanks to constant light control and presence detection
- For universal use for lighting offices, schools, traffic zones etc.
- Direct and indirect light can be controlled separately
- Variants with 1.5, 2.4 and 3.14 meter length available
- Housing Anodised aluminium
- Swiss Made

neva
lux

50 x 80 x 80 mm



elani connect P3200 3K

Product code 221111

ELANI

Technical Data

IDENTIFICATION	
Version	Presence detector
DIMENSIONS	
Dimensions L x W x H	50 x 80 x 80 mm
ELECTRICAL	
Mains connection	21 – 30 V
SENSOR TECHNOLOGY	
Max. mounting height	1,20 m
Sensor technology	passive infrared
With motion detector	Yes
Detection angle	180 °
Opening angle	90 °
Sneak-under protection	Yes
Segment-by-segment masking	No
Electronic scalability	Yes
Mechanical scalability	No
Radial range	r = 4 m (25 m²)
Tangential range	r = 12 m (226 m²)
Switching zones	96 switching zones
Mounting height	1 – 1,2 m
Presence range	r = 4 m (25 m²)
Optimal mounting height	1,2 m
CONNECTIVITY	
Networking	Yes
Type of networking	Master/master\nMaster/slave
Networking via	KNX bus
KNX functions	Photo-cell controller\nBasic light level function\nLight level\nHVAC output\nConstant-lighting control\nLight output 4x\nAir pressure\nHumidity output\nPresence output\nDay / night function\nDewpoint\nTemperature output\nLogic gate
With bus coupler	Yes
LIGHTING TECHNOLOGY	
Soft light start	Yes
Constant light regulation	Yes
SETTINGS	
Twilight switch	Yes
Twilight setting	2 – 1000 lx
Time setting	60 s – 255 Min.
Base light function	Yes
Functions	Presence detector logic
Settings via	ETS software\nRemote control\nBus\nSmart Remote
With remote control	Yes
Twilight setting teach	Yes
HOUSING & MATERIAL	
Protection class (IP)	IP20
Ambient temperature	from 0 up to 40 °C
Mounting location	wall
Application location	Indoors
Mounting type	Concealed wiring
Material	Plastic
Application room	Indoors WC / washroom corridor / aisle function room / ancillary room kitchenette one-person office stairwell
Colour	white
RAL colour	9010
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
Corner wall bracket included	No
CERTIFICATES & EPREL	
Certificates	EMC\nVDE
EPREL energy efficiency class	D

elani connect P3200 3K

Product code 221111

ELANI

Illustrations

MOUNTING HEIGHT



1 – 1,2 m BEREICH	1,2 m OPTIMAL	1,20 m MAX
----------------------	------------------	---------------

elani connect P3200 3K

Product code 221111

ELANI

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	221110	Connect PDC	Motion detector
	221102	elani Diffusor 3200 CDP	Cover
	221108	Emergency Package 1h (Astra)	Emergency lighting
	221343	elani Connector 90°	Coupler/connector L-shape
	221570	Connect TK2 BLM	Pushbutton interface
	221107	elani Link	Coupler/connector straight
	221397	elani Color RAL_NCS_3200	Other
	221109	Connect PD	Motion detector
	221997	elani WM-Set 3B	Mounting kit

ORDERING INFORMATION

Art.-Nr.221111

Typelani connect P3200 3K

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss