

elani C3200 TW

ELANI

neva
lux

3140 x 60 x 80 mm



elani C3200 TW

ELANI

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		Suitable for light band configuration	Yes
Source	woocommerce	Colour temperature	3000...5600 K	HOUSING & MATERIAL	
Product status	Normal	LED colour deviation	SDCM3	Protection class (IP)	IP20
Manufacturer	Nevalux	Colour rendering index	80-89	Protection class	II
DIMENSIONS		Illuminant	Yes, LED-System	Ambient temperature	-20...45 °C
Dimensions L x W x H	3140 x 60 x 80 mm	Luminous flux	8792 lm	Housing material	Aluminium
ELECTRICAL		Beam angle	105°	Cover material	Acrylic glass opal
Mains connection	200...240 V / 50 – 60 Hz	Luminaire luminous efficacy	112 lm/W	Mounting type	Ceiling / wall surface-mounted
Power	78,5 W	Glare value	UGR < 24	Colour	Aluminium
Replaceable driver	Yes	LIFETIME		SCOPE OF DELIVERY & WARRANTY	
Type of wiring	Suitable for through wiring	LED lifespan (25 °C)	50000 h	Manufacturer warranty	5 years
SENSOR TECHNOLOGY		SETTINGS		CERTIFICATES & EPREL	
With motion detector	No	DALI dimming	Yes	EPREL energy efficiency class	E
Nevalux sensor technology	DALI 2	With emergency light	No		
With light sensor	No				

elani C3200 TW

ELANI

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221102	elani Diffusor 3200 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221343	elani Connector 90°	Coupler/connector L-shape
 221397	elani Color RAL_NCS_3200	Other
 221107	elani Link	Coupler/connector straight
 221997	elani WM-Set 3B	Mounting kit

ORDERING INFORMATION

Art.-Nr.

221143

Typ

elani C3200 TW

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss