

elani C2400 TW

ELANI

neva
lux

2400 x 60 x 80 mm



elani C2400 TW

ELANI

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		Suitable for light band configuration			
Source	woocommerce	Colour temperature	3000...5600 K	Yes			
Product status	Normal	LED colour deviation	SDCM3				
Manufacturer	Nevalux	Colour rendering index	80-89				
DIMENSIONS		Illuminant	Yes, LED-System				
Dimensions L x W x H	2400 x 60 x 80 mm	Luminous flux	6720 lm				
		Beam angle	105°				
ELECTRICAL		Luminaire luminous efficacy	112 lm/W				
Mains connection	200...240 V / 50 – 60 Hz	Glare value	UGR < 24				
Power	60 W	LIFETIME					
Replaceable driver	Yes	LED lifespan (25 °C)	50000 h				
Type of wiring	Suitable for through wiring	SETTINGS					
SENSOR TECHNOLOGY		DALI dimming	Yes				
With motion detector	No	With emergency light	No				
Nevalux sensor technology	DALI 2						
With light sensor	No						
				HOUSING & MATERIAL			
				Protection class (IP)	IP20		
				Protection class	II		
				Ambient temperature	-20...45 °C		
				Housing material	Aluminium		
				Cover material	Acrylic glass opal		
				Mounting type	Ceiling / wall surface-mounted		
				Colour	Aluminium		
				SCOPE OF DELIVERY & WARRANTY			
				Manufacturer warranty	5 years		
				CERTIFICATES & EPREL			
				EPREL energy efficiency class	E		

elani C2400 TW

ELANI

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221101	elani Diffusor 2500 CDP	
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221343	elani Connector 90°	Coupler/connector L-shape
 221396	elani Color RAL_NCS_2400	Other
 221107	elani Link	Coupler/connector straight
 221996	elani WM-Set 2B	Mounting kit

ORDERING INFORMATION

Art.-Nr.

221137

Typ

elani C2400 TW

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss