

fayola 125 On-Off 4K

FAYOLA 100-205

neva
lux

155 x 111 mm



fayola 125 On-Off 4K

FAYOLA 100-205

Technical Data

IDENTIFICATION		SENSOR TECHNOLOGY		SETTINGS	
Source	woocommerce	With motion detector	No	DALI dimming	No
Product status	Normal	Nevalux sensor technology	On / Off	HOUSING & MATERIAL	
Successor	221447	LIGHTING TECHNOLOGY		Protection class (IP)	IP20
Manufacturer	Nevalux	Colour temperature	4000 K	Protection class	II
DIMENSIONS		LED colour deviation	SDCM3	Ambient temperature	-20...40 °C
Dimensions Ø × H	155 x 111 mm	Colour rendering index	80-89	Housing material	Aluminum
Drill hole	125 mm	Illuminant	LED	Cover material	Diffusor opal
ELECTRICAL		Luminous flux	1400 lm	Mounting type	In-ceiling installation
Mains connection	220...240 V / 50 – 60 Hz	Beam angle	70°	Colour	White
Power	15 W	Luminaire luminous efficacy	93 lm/W	SCOPE OF DELIVERY & WARRANTY	
Replaceable driver	Yes	Glare value	UGR < 19	Manufacturer warranty	5 years
Type of wiring	Ending	LIFETIME		CERTIFICATES & EPREL	
LED rated current	350 mA	LED lifespan (25 °C)	50000 h	EPREL energy efficiency class	F

fayola 125 On-Off 4K

FAYOLA 100-205

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220432	fayola 100 On-Off 4K	
 220434	fayola 150 On-Off 4K	
 220435	fayola 175 On-Off 4K	
 220436	fayola 205 On-Off 4K	
 220721	Emergency Package 1h (50V/2.5W/Box)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.

220433

Typ

fayola 125 On-Off 4K

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss