

zwena DALI C350 3K

ZWENA CONNECT C

neva
lux

- For universal use for illumination of offices, schools, traffic zones, etc.
- Optionally as an intelligent Connect version with or without motion sensor, or as a conventional DALI luminaire
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- High quality finish
- Direct and indirect light distribution

350 x 82 mm



zwena DALI C350 3K

ZWENA CONNECT C

Technical Data

IDENTIFICATION		With light sensor		No	With emergency light		No
Source	woocommerce	LIGHTING TECHNOLOGY					
Product status	Normal	Colour temperature	3000 K				
Manufacturer	Nevalux	LED colour deviation	SDCM3				
DIMENSIONS		Colour rendering index	80-89				
Dimensions Ø × H	350 x 82 mm	Illuminant	LED				
ELECTRICAL		Luminous flux	1700 lm (Down 1200, Up 500)				
Mains connection	200...240 V / 50 – 60 Hz	Beam angle	Down 95°, Up 100°				
Power	18 W	Luminaire luminous efficacy	94 lm/W				
Replaceable driver	Yes	Glare value	UGR < 18				
		LIFETIME					
Type of wiring	Suitable for through wiring	LED lifespan (25 °C)	50000 h				
SENSOR TECHNOLOGY		SETTINGS					
With motion detector	No	DALI dimming	Yes				
Nevalux sensor technology	DALI 2						

HOUSING & MATERIAL	
Protection class (IP)	IP20
Protection class	I
Ambient temperature	-20...45 °C
Housing material	Aluminum
Cover material	Microprismatic acrylic glass
Mounting type	Ceiling / wall surface-mounted
Colour	White
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
EPREL energy efficiency class	F

zwena DALI C350 3K

ZWENA CONNECT C

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220571	zwena DALI C450 3K	
 220573	zwena DALI C600 3K	
 220575	zwena DALI C900 3K	
 220692	Emergency Package 1h (50V/1.5W/Compact)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.

220569

Typ

zwena DALI C350 3K

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss