

nayo P 4K

NAYO P 4K

neva
lux

1190 x 160 x 30 mm



nayo P 4K

NAYO P 4K

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		Direct/indirect ratio separately controllable		No
Source	woocommerce	Colour temperature	4000 K	Constant light output control		Yes
Product status	Normal	LED colour deviation	SDCM3			
Manufacturer	Nevalux	Colour rendering index	80-89			
DIMENSIONS		Illuminant	LED	HOUSING & MATERIAL		
Dimensions L × W × H	1190 x 160 x 30 mm	Luminous flux	6700 lm (Down 3400, Up 3300)	Protection class (IP)	IP20	
Suspension length	1500 mm	Beam angle	Down 50°, Up 115°	Protection class	I	
ELECTRICAL		Luminaire luminous efficacy	112 lm/W	Ambient temperature	-20...45 °C	
Mains connection	200...240 V / 50 – 60 Hz	Glare value	UGR < 10	Housing material	Aluminum	
Power	60 W	LIFETIME		Cover material	Darklight Optics	
Replaceable driver	Yes	LED lifespan (25 °C)	50000 h	Mounting type	Ceiling pendant	
Type of wiring	Through wiring included	SETTINGS		Colour	White	
SENSOR TECHNOLOGY		DALI dimming	Yes	SCOPE OF DELIVERY & WARRANTY		
With motion detector	No	With emergency light	No	Manufacturer warranty	5 years	
Nevalux sensor technology	DALI 2	Suitable for light band configuration	Yes	CERTIFICATES & EPREL		
With light sensor	No			EPREL energy efficiency class	E	

nayo P 4K

NAYO P 4K

Accessories

ORDERING INFORMATION

Art.-Nr. 220175

Typ nayo P 4K

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss