

RS PRO P3 SP warmweiss

P-SERIE

neva
lux

400 x 142 mm



RS PRO P3 SP warmweiss

P-SERIE

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		HOUSING & MATERIAL	
Source	woocommerce	Measured luminous flux 360°	2081 lm	Impact resistance	IK03
Product status	Normal	Colour temperature	3000 K	Protection class (IP)	IP54
Manufacturer	Nevalux	Illuminant	LED cannot be replaced	Protection class	II
DIMENSIONS		Base	without	Ambient temperature	from -10 up to 40 °C
Dimensions Ø × H	400 x 142 mm	LED cooling system	Passive Thermo Control	Housing material	Plastic
ELECTRICAL		Soft light start	Yes	Cover material	Plastic, opal
Mains connection	220 – 240 V / 50 – 60 Hz	LIFETIME		Mounting location	wall\ncelling
Power	17,8 W	LED lifetime max. °C	50000 h	Colour	white
SENSOR TECHNOLOGY		LED lifetime L70B50 25°C	> 60000 h	SCOPE OF DELIVERY & WARRANTY	
With motion detector	No	Luminous flux decline per LM80	L80B10	Manufacturer warranty	5 years
CONNECTIVITY				CERTIFICATES & EPREL	
Networking via	Cable			Certificates	DEKRA

RS PRO P3 SP warmweiss

P-SERIE

Accessories

ORDERING INFORMATION	
Art.-Nr.	221814
Typ	RS PRO P3 SP warmweiss
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	