

aluna connect LS C910 4K

ALUNA

neva
lux

910 x 118 mm



aluna connect LS C910 4K

ALUNA

Technical Data

IDENTIFICATION	
Source	woocommerce
Product status	Normal
Manufacturer	Nevalux
DIMENSIONS	
Dimensions Ø × H	910 x 118 mm
ELECTRICAL	
Mains connection	200...240 V / 50 – 60 Hz
Power	78 W
Replaceable driver	Yes
Type of wiring	Suitable for through wiring
SENSOR TECHNOLOGY	
With motion detector	No
Nevalux sensor technology	Smartlink, BT SIG Mesh
With light sensor	Yes
CONNECTIVITY	
With radio network control	Yes
LIGHTING TECHNOLOGY	
Colour temperature	4000 K
LED colour deviation	SDCM3
Colour rendering index	80-89
Illuminant	LED
Luminous flux	9800 lm (Down 8430, Up 1370)
Beam angle	105°
Luminaire luminous efficacy	125 lm/W
Glare value	UGR < 21
LIFETIME	
LED lifespan (25 °C)	70000 h
SETTINGS	
DALI dimming	Yes
With emergency light	No
Direct/indirect ratio separately controllable	No
With program-controlled lighting control	Yes
HOUSING & MATERIAL	
Protection class (IP)	IP20
Protection class	I
Ambient temperature	-20...45 °C
Housing material	Steel
Cover material	Acrylic glass opal
Mounting type	Ceiling surface-mounted
Colour	White
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
EPREL energy efficiency class	D

aluna connect LS C910 4K

ALUNA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221105	ayana Diffusor 850 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221570	Connect TK2 BLM	Pushbutton interface
 221846	aluna Color RAL_NCS_0910	Other
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

222019

Typ

aluna connect LS C910 4K

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss