

RS PRO P1 warm white

LED INDOOR LIGHT WITHOUT SENSOR

neva
lux

EAN 4007841056056

280 x 110 mm



RS PRO P1 warm white

LED INDOOR LIGHT WITHOUT SENSOR

EAN 4007841056056

Technical Data

IDENTIFICATION	
PU1 EAN	4007841056056
Material number	110081891
SAP designation	LED INNENLEUCHTE RS PRO P1 WW
Product name data sheet	RS PRO P1 warm white
Product category	LED indoor light without sensor
Discount group	I
Source	Steinel Excel
Product status	Normal
Manufacturer	Steinel
DIMENSIONS	
Dimensions Ø × H	280 x 110 mm
PU1 net weight	0.37
ELECTRICAL	
Mains connection	220 – 240 V / 50 – 60 Hz
Power	8,3 W
B10 fuse (pcs)	54
B16 fuse (pcs)	87
C10 fuse (pcs)	90
C16 fuse (pcs)	145
Maximum inrush current	13 A

SENSOR TECHNOLOGY	
With motion detector	No
CONNECTIVITY	
Networking via	Cable
LIGHTING TECHNOLOGY	
Measured luminous flux 360°	953 lm
Colour temperature	3000 K
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
Soft light start	Yes
Photobiological safety per EN 62471	RG1
LIFETIME	
LED lifetime max. °C	50000 h
LED lifetime L70B50 25°C	> 60000 h
Luminous flux decline per LM80	L80B10
LED lifetime per IEC 62717 L70	100.000 h
LED lifetime per IEC 62717 L80	73.000 h

LED lifetime per IES TM-21 L70	>60.000 h
LED lifetime per IES TM-21 L80	>60.000 h
SETTINGS	
Main light adjustable	No
HOUSING & MATERIAL	
Impact resistance	IK03
Protection class (IP)	IP54
Protection class	II
Ambient temperature	from -10 up to 40 °C
Housing material	Plastic
Cover material	Plastic, opal
Mounting location	wall ceiling
Colour	white
Protection class ceiling	IP54
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
Certificates	DEKRA
EPREL category	Surrounded product with integrated light source


RS PRO P1 warm white

EAN 4007841056056

LED INDOOR LIGHT WITHOUT SENSOR

Illustrations

TECHNICAL DRAWINGS



280 x 110 mm


RS PRO P1 warm white

EAN 4007841056056

LED INDOOR LIGHT WITHOUT SENSOR


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Master/slave interconnection circuit diagram

RS PRO P1 warm white


EAN 4007841056056

LED INDOOR LIGHT WITHOUT SENSOR

Highlights



Including STEINEL LED system



Intelligent soft light start



Interconnectable by cable (maximum of 10 units)

RS PRO P1 warm white

LED INDOOR LIGHT WITHOUT SENSOR

EAN 4007841056056

Accessories

ORDERING INFORMATION	
Art.-Nr.	056056
EAN	4007841056056
Typ	RS PRO P1 warm white
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	