

anele connect C620

ANELE CONNECT

neva
lux

620 x 620 x 8.5 mm (Einbautiefe: 40 mm)



anele connect C620

ANELE CONNECT

Technical Data

IDENTIFICATION	
Source	woocommerce
Product status	Normal
Manufacturer	Nevalux
DIMENSIONS	
Dimensions L x W x H	620 x 620 x 8.5 mm (Einbautiefe: 40 mm)
ELECTRICAL	
Mains connection	200...240 V / 50 – 60 Hz
Power	33 W
Replaceable driver	Yes
Type of wiring	Suitable for through wiring
SENSOR TECHNOLOGY	
Sensor technology	passive infrared
With motion detector	Yes
Detection angle	360°
Radial range	4 x 4 m (16 m²)
Tangential range	6 x 6 m (36 m²)
Mounting height	< 10 m
Presence range	4 x 4 m (16 m²)
Nevalux sensor technology	Smartlink, BT SIG Mesh
With light sensor	Yes
CONNECTIVITY	
With radio network control	Yes
LIGHTING TECHNOLOGY	
Colour temperature	4000 K
LED colour deviation	SDCM3
Colour rendering index	80-89
Illuminant	LED
Luminous flux	3960 lm
Beam angle	90°
Luminaire luminous efficacy	120 lm/W
Glare value	UGR < 19
LIFETIME	
LED lifespan (25 °C)	50000 h
SETTINGS	
DALI dimming	Yes
With emergency light	No
Suitable for light band configuration	No
With program-controlled lighting control	Yes
HOUSING & MATERIAL	
Protection class (IP)	IP20
Protection class	I
Ambient temperature	-20...45 °C
Housing material	Aluminum
Cover material	Microprismatic acrylic glass
Mounting type	In-ceiling installation
Colour	White
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
EPREL energy efficiency class	E

anele connect C620

ANELE CONNECT

Illustrations


MOUNTING HEIGHT

< 10 m BEREICH

anele connect C620

ANELE CONNECT

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221638	anele APG 595	Installation housing
 221639	anele APG 620	Installation housing
 221640	anele DEF	Mounting kit
 221641	anele P-Set	Suspension cable
 220721	Emergency Package 1h (50V/2.5W/Box)	Emergency lighting
 221570	Connect TK2 BLM	Pushbutton interface
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
		

ORDERING INFORMATION

Art.-Nr.221635

Typanele connect C620

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss