

# zwena connect LS P600 3K

ZWENA CONNECT P

neva  
lux

- For universal use for illumination of offices, schools, traffic zones, etc.
- Optionally as an intelligent Connect version with or without motion sensor, or as a conventional DALI luminaire
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- High quality finish
- Direct and indirect light distribution

600 x 82 mm



# zwena connect LS P600 3K

ZWENA CONNECT P


## Technical Data

| IDENTIFICATION            |                             | CONNECTIVITY                |                              | Direct/indirect ratio separately controllable |                              |
|---------------------------|-----------------------------|-----------------------------|------------------------------|-----------------------------------------------|------------------------------|
| Source                    | woocommerce                 | With radio network control  | Yes                          |                                               | No                           |
| DIMENSIONS                |                             | LIGHTING TECHNOLOGY         |                              | With program-controlled lighting control      | Yes                          |
| Product status            | Normal                      | Colour temperature          | 3000 K                       | Constant light output control                 | Yes                          |
| Successor                 | 222059                      | LED colour deviation        | SDCM3                        | HOUSING & MATERIAL                            |                              |
| Manufacturer              | Nevalux                     | Colour rendering index      | 80-89                        | Protection class (IP)                         | IP20                         |
|                           |                             | Illuminant                  | LED                          | Protection class                              | I                            |
|                           |                             | Luminous flux               | 5250 lm (Down 3500, Up 1750) | Ambient temperature                           | -20...45 °C                  |
|                           |                             | Beam angle                  | Down 95°, Up 100°            | Housing material                              | Aluminum                     |
|                           |                             | Luminaire luminous efficacy | 109 lm/W                     | Cover material                                | Microprismatic acrylic glass |
|                           |                             | Glare value                 | UGR < 18                     | Mounting type                                 | Ceiling pendant              |
| ELECTRICAL                |                             | LIFETIME                    |                              | Colour                                        | White                        |
| Mains connection          | 200...240 V / 50 – 60 Hz    | LED lifespan (25 °C)        | 50000 h                      | SCOPE OF DELIVERY & WARRANTY                  |                              |
| Power                     | 48 W                        | SETTINGS                    |                              | Manufacturer warranty                         | 5 years                      |
| Replaceable driver        | Yes                         | DALI dimming                | Yes                          | CERTIFICATES & EPREL                          |                              |
| Type of wiring            | Suitable for through wiring | With emergency light        | No                           | EPREL energy efficiency class                 | E                            |
| LED rated current         | 1300 mA                     |                             |                              |                                               |                              |
| SENSOR TECHNOLOGY         |                             |                             |                              |                                               |                              |
| With motion detector      | No                          |                             |                              |                                               |                              |
| Nevalux sensor technology | Smartlink, BT SIG Mesh      |                             |                              |                                               |                              |
| With light sensor         | Yes                         |                             |                              |                                               |                              |

# zwena connect LS P600 3K

ZWENA CONNECT P

## Accessories

| ARTICLE NUMBER                                                                            | DESCRIPTION                                 | CATEGORY             |
|-------------------------------------------------------------------------------------------|---------------------------------------------|----------------------|
|  221618   | Emergency Package 1h (50V/3.5W)             | Emergency lighting   |
|  221570   | Connect TK2 BLM                             | Pushbutton interface |
|  221591   | Smartlink T-Board PB4                       | Wireless push-button |
|  221970  | Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2 | Wireless push-button |
|  221971 | Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4 | Wireless push-button |

ORDERING INFORMATION

Art.-Nr.

221552

Typ

zwena connect LS P600 3K

neva  
lux

nevalux AG  
Neugrütstrasse 2  
8610 Uster  
+41 44 508 78 78  
info@nevalux.swiss