

asali B1500 4K DALI 120

ASALI

neva
lux

Product code 221609

- Universal luminaire insert for professional refurbishment of continuous rows with T5 or T8 fluorescent tubes
- Fits most of the trunking systems available on the market
- Available as intelligent Connect version or as conventional DALI luminaire
- Up to 95% energy savings with Connect luminaires thanks to constant light control and presence detection
- Very high luminaire efficiency with approx. 160 lumens per watt
- Also available as office variant with UGR <19

neva
lux

1528 x 64.7 x 30 mm



asali B1500 4K DALI 120

ASALI

Product code 221609

Technical Data


DIMENSIONS		LIGHTING TECHNOLOGY		Suitable for light band configuration	Yes
Dimensions L x W x H	1528 x 64.7 x 30 mm	Colour temperature	4000 K		
ELECTRICAL		LED colour deviation	SDCM3	HOUSING & MATERIAL	
Mains connection	200...240 V / 50 – 60 Hz	Colour rendering index	80-89	Protection class (IP)	IP40
Power	68 W	Illuminant	LED	Protection class	I
Replaceable driver	Yes	Luminous flux	10880 lm	Ambient temperature	-20...45 °C
Type of wiring	Through wiring included	Beam angle	120°	Housing material	Aluminum
LED rated current	310 mA	Luminaire luminous efficacy	160 lm/W	Cover material	Lens transparent
Maximum number of luminaires per circuit breaker	C10: 15x, C16: 24x, C25: 37x, B10: 9x , B16: 14x, B25: 22x	Glare value	UGR < 26	Mounting type	Use in continuous row
SENSOR TECHNOLOGY		LIFETIME		Colour	white
With motion detector	No	LED lifespan (25 °C)	50000 h	SCOPE OF DELIVERY & WARRANTY	
With light sensor	No	SETTINGS		Manufacturer warranty	5 years
		DALI dimming	Yes	CERTIFICATES & EPREL	
		With emergency light	No	EPREL energy efficiency class	C

asali B1500 4K DALI 120

ASALI

Product code 221609

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221611	asali WAGO Male	Plug/Clamp
 221612	asali WAGO Female	Plug/Clamp
 221613	asali extension 5x 1.6	Connecting cable
 221614	asali extension 5x 3.2	Connecting cable
 221615	asali extension 7x 1.6	Connecting cable
 221616	asali extension 7x 3.2	Connecting cable
 221617	asali Blindcover	Cover
 220688	Emergency Package 1h (250V/3.5W)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.221609

Typasali B1500 4K DALI 120

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss