

iFux CityStreet4 60W DM10 3K

IFUX CITYSTREET 4

neva
lux

- The iFux CityStreet 4 luminaire is an intelligent and functional street light of the latest generation. It convinces by very good corrosion protection and best maintenance characteristics. Variable candelabra diameters ensure universal use.

458 x 240 x 100 mm



iFux CityStreet4 60W DM10 3K

IFUX CITYSTREET 4

Technical Data

IDENTIFICATION		With light sensor		No	HOUSING & MATERIAL	
Variant	Wide beam DM10, 60W	CONNECTIVITY			Impact resistance	IK09
Source	woocommerce	With radio network control		No	Protection class (IP)	IP66
Product status	Normal	LIGHTING TECHNOLOGY			Protection class	II
Manufacturer	Nevalux	Colour temperature		3000...3000 K	Ambient temperature	-30...55 °C
DIMENSIONS		Colour rendering index		70-79	Housing material	Aluminium
Dimensions L x W x H	458 x 240 x 100 mm	Luminous flux		8520 lm	Cover material	Clear glass
Suitable for pole-top diameter	48...76 mm	Beam angle		Medium	Mounting type	Column Post-top/side-entry
ELECTRICAL		Luminaire luminous efficacy		142 lm/W	Colour	Anthracite
Mains connection	90...264 VAC / 47 – 63 Hz	LIFETIME			SCOPE OF DELIVERY & WARRANTY	
Power	60 W	LED lifespan (25 °C)		100000 h	Manufacturer warranty	5 years
Power factor	0.92	SETTINGS			With connection cable	Yes
SENSOR TECHNOLOGY		DALI dimming		Yes	CERTIFICATES & EPREL	
With motion detector	No	With program-controlled lighting control		No	EPREL energy efficiency class	A++, A+, A (LED)
Nevalux sensor technology	E-Save					

iFux CityStreet4 60W DM10 3K

IFUX CITYSTREET 4

Accessories

ORDERING INFORMATION	
Art.-Nr.	221187
Typ	iFux CityStreet4 60W DM10 3K
neva lux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	