

IR Quattro HD 24m DALI plus Surface wiring

neva
lux**PRESENCE DETECTOR**

EAN 4007841035273

65 x 120 x 120 mm



IR Quattro HD 24m DALI plus Surface wiring

PRESENCE DETECTOR

EAN 4007841035273

Technical Data

IDENTIFICATION			
PU1 EAN	4007841035273	Electronic scalability	No
Material number	110053593	Mechanical scalability	Yes
SAP designation	PRAESENZMELDER IR QUATTRO HD DALIPLUS AP	Radial range	8 x 8 m (64 m²)
Version	Presence detector	Tangential range	20 x 20 m (400 m²)
Product name data sheet	IR Quattro HD 24m DALI plus Surface wiring	Switching zones	4800 switching zones
Product category	Presence detector	Mounting height	2,50 – 10,00 m
Discount group	P	Presence range	8 x 8 m (64 m²)
Source	Steinel Excel	Optimal mounting height	2,8 m
Product status	Normal	Nevalux sensor technology	DALI 2
Manufacturer	Steinel	CONNECTIVITY	
DIMENSIONS		Networking	Yes
Dimensions L x W x H	65 x 120 x 120 mm	Type of networking	Master/master Master/slave
PU1 net weight	0.289	Networking via	Cable DALI bus
ELECTRICAL		LIGHTING TECHNOLOGY	
Mains connection	220 – 240 V / 50 – 60 Hz	Soft light start	Yes
Own consumption	0,5 W	Continuous light	selectable
Control output DALI	Broadcast 64 electronic ballasts / Addressable	Constant light regulation	Yes
Maximum inrush current	10 A	SETTINGS	
SENSOR TECHNOLOGY		Twilight switch	Yes
Max. mounting height	10,00 m	Twilight setting	10 – 1000 lx
Sensor technology	passive infrared	Time setting	5 s – 60 Min.
With motion detector	Yes	Base light function	Yes
Detection angle	360 °	Base light function time	1-60 min, all night
Opening angle	160 °	Main light adjustable	50 - 100 %
Sneak-under protection	Yes	Functions	4 inputs for conventional switches Semi-/fully automatic Constant-lighting control ON-OFF Master/slave override Neighbouring group function Normal / test mode TouchDIM function
Segment-by-segment masking	No		
		Settings via	Remote control Smart Remote
		With remote control	No
		Twilight setting teach	Yes
		Base light function in percent	10 – 50 %
		Base light function percent from	10
		Base light function percent to	50
		HOUSING & MATERIAL	
		Protection class (IP)	IP20
		Ambient temperature	from 0 up to 40 °C
		Mounting location	ceiling
		Application location	Indoors
		Mounting type	Surface wiring
		Material	Plastic
		Application room	classroom lecture hall open-plan office high-bay warehouse production facilities conference room / meeting room duty room recreation room changing room sports hall reception / lobby multi-storey / underground car park Indoors
		Colour	white
		RAL colour	9010
		SCOPE OF DELIVERY & WARRANTY	
		Manufacturer warranty	5 years
		Corner wall bracket included	No
		CERTIFICATES & EPREL	
		Certificates	VDE DALI-2


IR Quattro HD 24m DALI plus Surface wiring

PRESENCE DETECTOR

EAN 4007841035273

Illustrations

TECHNICAL DRAWINGS



65 x 120 x 120 mm

MOUNTING HEIGHT

2,50 – 10,00 m BEREICH	2,8 m OPTIMAL	10,00 m MAX
---------------------------	------------------	----------------


IR Quattro HD 24m DALI plus Surface wiring

PRESENCE DETECTOR

EAN 4007841035273


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Master circuit diagram with electronic ballast OFF

IR Quattro HD 24m DALI plus Surface wiring

EAN 4007841035273

PRESENCE DETECTOR

Highlights



4 pyros with DSP (Digital Signal Processing)



Smart Remote remote control optional

IR Quattro HD 24m DALI plus Surface wiring

EAN 4007841035273

PRESENCE DETECTOR

Accessories

ORDERING INFORMATION

Art.-Nr. 035273

EAN 4007841035273

Typ IR Quattro HD 24m DALI plus Surface wiring

**neva
lux**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss