

L 400 S black

E27 SENSOR-SWITCHED OUTDOOR LIGHT

neva
lux

EAN 4007841611019

250 x 215 x 336 mm



L 400 S black

EAN 4007841611019

E27 SENSOR-SWITCHED OUTDOOR LIGHT

Technical Data

IDENTIFICATION					
PU1 EAN	4007841611019	Opening angle	180 °	Settings via	Potentiometers
Material number	103266203	Sneak-under protection	Yes	With remote control	No
SAP designation	AUSSENLEUCHTE L 400 S SW	Segment-by-segment masking	Yes	Base light function in percent	0 – 50 %
Product name data sheet	L 400 S black	Electronic scalability	No	Base light function percent from	0
Product category	E27 Sensor-switched outdoor light	Mechanical scalability	No	Base light function percent to	50
Discount group	A	Radial range	r = 3 m (19 m²)	HOUSING & MATERIAL	
Source	Steinel Excel	Tangential range	r = 12 m (302 m²)	Impact resistance	IK03
Product status	Normal	Mounting height	1,80 – 6,00 m	Protection class (IP)	IP44
Manufacturer	Steinel	Optimal mounting height	2 m	Protection class	II
DIMENSIONS		CONNECTIVITY		Ambient temperature	from -20 up to 40 °C
Dimensions L x W x H	250 x 215 x 336 mm	Networking	No	Housing material	Plastic
PU1 net weight	1.149	Slave mode adjustable	No	Cover material	Glass transparent
ELECTRICAL		LIGHTING TECHNOLOGY		Cover material (scope of delivery)	shrouds
Mains connection	220 – 240 V / 50 – 60 Hz	With illuminant	No	Mounting location	wall
Power	60 W	Illuminant	All-purpose lamp	Application location	Outdoors
Own consumption	0,8 W	Base	E27	Mounting type	Surface wiring
SENSOR TECHNOLOGY		Soft light start	Yes	Application room	outdoors front door all round the building terrace / balcony courtyard & driveway
Max. mounting height	6,00 m	Continuous light	selectable, 4h	SCOPE OF DELIVERY & WARRANTY	
Sensor technology	passive infrared	SETTINGS		Colour	black
With motion detector	Yes	Twilight switch	Yes	Manufacturer warranty	
Detection angle	240 °	Twilight setting	2 – 2000 lx	5 years	
		Time setting	5 s – 15 Min.		
		Base light function	Yes		


L 400 S black

E27 SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841611019

Illustrations

TECHNICAL DRAWINGS



250 x 215 x 336 mm

MOUNTING HEIGHT

1,80 – 6,00 m BEREICH	2 m OPTIMAL	6,00 m MAX
--------------------------	----------------	---------------


L 400 S black

EAN 4007841611019

E27 SENSOR-SWITCHED OUTDOOR LIGHT

Wiring Diagrams

WIRING DIAGRAM 1



Slave/wireless master interconnection circuit diagram

L 400 S black

EAN 4007841611019

E27 SENSOR-SWITCHED OUTDOOR LIGHT

Highlights



Crystal glass shade



Optional basic lighting level 0 - 50 %



UV-resistant plastic

L 400 S black

E27 SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841611019

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841630317	Eckwandhalter 03	Accessory

ORDERING INFORMATION

Art.-Nr.

611019

EAN

4007841611019

Typ

L 400 S black

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss