

ayana connect LS C850 4K

AYANA

neva
lux

850 x 95 mm



ayana connect LS C850 4K

AYANA

Technical Data

IDENTIFICATION		CONNECTIVITY		Direct/indirect ratio separately controllable	No
Source	woocommerce	With radio network control	Yes	With program-controlled lighting control	Yes
DIMENSIONS		LIGHTING TECHNOLOGY		HOUSING & MATERIAL	
Product status	Normal	Colour temperature	4000 K	Protection class (IP)	IP20
Manufacturer	Nevalux	LED colour deviation	SDCM3	Protection class	I
Dimensions Ø × H		Colour rendering index	80-89	Ambient temperature	-20...45 °C
ELECTRICAL		Illuminant	LED	Housing material	Steel
Mains connection	200...240 V / 50 – 60 Hz	Luminous flux	9800 lm (Down 8430, Up 1370)	Cover material	Acrylic glass opal
Power	78 W	Beam angle	105°	Mounting type	Ceiling / wall surface-mounted
Replaceable driver	Yes	Luminaire luminous efficacy	125 lm/W	Colour	White
Type of wiring	Suitable for through wiring	Glare value	UGR < 21	SCOPE OF DELIVERY & WARRANTY	
SENSOR TECHNOLOGY		LIFETIME		Manufacturer warranty	5 years
With motion detector	No	LED lifespan (25 °C)	70000 h	CERTIFICATES & EPREL	
Nevalux sensor technology	Smartlink, BT SIG Mesh	SETTINGS		EPREL energy efficiency class	D
With light sensor	Yes	DALI dimming	Yes		
		With emergency light	No		

ayana connect LS C850 4K

AYANA

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221105	ayana Diffusor 850 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221570	Connect TK2 BLM	Pushbutton interface
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

222010

Typ

ayana connect LS C850 4K

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss