

zwena DALI P600 4K

ZWENA CONNECT P

neva
lux

600 x 82 mm



zwena DALI P600 4K

ZWENA CONNECT P

Technical Data

IDENTIFICATION	
Source	woocommerce
Product status	Normal
Manufacturer	Nevalux
DIMENSIONS	
Dimensions Ø × H	600 x 82 mm
Suspension length	1500 mm
ELECTRICAL	
Mains connection	200...240 V / 50 – 60 Hz
Power	48 W
Replaceable driver	Yes
Type of wiring	Suitable for through wiring
LED rated current	1300 mA
SENSOR TECHNOLOGY	
With motion detector	No
Nevalux sensor technology	DALI 2

With light sensor	No
LIGHTING TECHNOLOGY	
Colour temperature	4000 K
LED colour deviation	SDCM3
Colour rendering index	80-89
Illuminant	LED
Luminous flux	5250 lm (Down 3500, Up 1750)
Beam angle	Down 95°, Up 100°
Luminaire luminous efficacy	109 lm/W
Glare value	UGR < 18
LIFETIME	
LED lifespan (25 °C)	50000 h
SETTINGS	
DALI dimming	Yes

With emergency light	No
Direct/indirect ratio separately controllable	No
HOUSING & MATERIAL	
Protection class (IP)	IP20
Protection class	I
Ambient temperature	-20...45 °C
Housing material	Aluminum
Cover material	Microprismatic acrylic glass
Mounting type	Ceiling pendant
Colour	White
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
EPREL energy efficiency class	E

zwena DALI P600 4K

ZWENA CONNECT P

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220578	zwena DALI P350 4K	
 220580	zwena DALI P450 4K	
 220584	zwena DALI P900 4K	
 221618	Emergency Package 1h (50V/3.5W)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.

220582

Typ

zwena DALI P600 4K

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss