

MD IR N360 COM1 - Surface wiring anthracite

neva
lux

MOTION DETECTOR

EAN 4007841079888

- An even closer view of access areas: ideal solution for building entrances and façades
- Eagle Eye technology extends the individual detection area with frontal walking direction towards the sensor
- Power max. 600 W (LED-ready)
- Sensor family with three detection areas: Wall mounting 130° or 270° and ceiling mounting with 360°, optionally as surface-mounted or recessed version
- Commissioning, settings and networking via Bluetooth Mesh
- Comprehensive Connect functionalities, such as control of connected outdoor lights, definition of timer programmes and integration of wireless push-buttons

80 x 93 mm



MD IR N360 COM1 - Surface wiring anthracite

EAN 4007841079888

MOTION DETECTOR

Technical Data

IDENTIFICATION

PU1 EAN	4007841079888
Material number	110083244
SAP designation	BEWEGUNGSMELDER MD IR N360 COM1 AP ANT
Version	Motion detectors
Product name data sheet	MD IR N360 COM1 - Surface wiring anthracite
Product category	Motion detector
Discount group	B
Source	Steinel Excel
Product status	Product announcement
Manufacturer	Steinel

DIMENSIONS

Dimensions L x W x H	93 x 80 x 80 mm
Dimensions Ø x H	80 x 93 mm
PU1 net weight	0.165

ELECTRICAL

Mains connection	50 – 60 Hz
Power	0,5 W
Fluorescent lamps ECG	600 W
Fluorescent lamps series-compensated	1000 VA

Capacitive load in μF **176 μF**

SENSOR TECHNOLOGY

Max. mounting height	6,00 m
Sensor technology	passive infrared
With motion detector	Yes
Detection angle	360 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	Yes
Mechanical scalability	No
Radial range	Ø 7 m (38 m²)
Tangential range	Ø 26 m (531 m²)
Switching zones	1179 switching zones
Mounting height	1,8 – 6,00 m
Optimal mounting height	2,5 m
Nevalux sensor technology	BT SIG Mesh, On / Off

CONNECTIVITY

Networking	Yes
Networking via	Bluetooth Mesh

LIGHTING TECHNOLOGY

Continuous light **selectable**

Constant light regulation	No
---------------------------	----

SETTINGS

Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Settings via	Bluetooth App
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL

Protection class (IP)	IP54
Ambient temperature	from -20 up to 40 °C
Cover material (scope of delivery)	Cover clips
Application location	Outdoors
Mounting type	Surface wiring
Material	Plastic
Colour	Anthracite
RAL colour	7016

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
Corner wall bracket included	No


MD IR N360 COM1 - Surface wiring anthracite

MOTION DETECTOR

EAN 4007841079888

Illustrations

TECHNICAL DRAWINGS



80 x 93 mm

MOUNTING HEIGHT

1,8 – 6,00 m BEREICH	2,5 m OPTIMAL	6,00 m MAX
-------------------------	------------------	---------------


MD IR N360 COM1 - Surface wiring anthracite

EAN 4007841079888

MOTION DETECTOR

Wiring Diagrams

WIRING DIAGRAM 1



3-wire circuit diagram

MD IR N360 COM1 - Surface wiring anthracite

MOTION DETECTOR

EAN 4007841079888

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841067335	Relais REL5A-Bluetooth	System components
 4007841067342	Tasterkoppler PC4-Bluetooth	System components

ORDERING INFORMATION

Art.-Nr.

079888

EAN

4007841079888

Typ

MD IR N360 COM1 - Surface wiring anthracite

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss