

fayola 100 DALI 4K

FAYOLA 100-205

neva
lux

120 x 101 mm



fayola 100 DALI 4K

FAYOLA 100-205

Technical Data

IDENTIFICATION		SENSOR TECHNOLOGY		SETTINGS	
Source	woocommerce	With motion detector	No	DALI dimming	Yes
Product status	Normal	Nevalux sensor technology	DALI 2	HOUSING & MATERIAL	
Successor	221446	LIGHTING TECHNOLOGY		Protection class (IP)	IP20
Manufacturer	Nevalux	Colour temperature	4000 K	Protection class	II
DIMENSIONS		LED colour deviation	SDCM3	Ambient temperature	-20...40 °C
Dimensions Ø × H	120 x 101 mm	Colour rendering index	80-89	Housing material	Aluminum
Drill hole	90 mm	Illuminant	LED	Cover material	Diffusor opal
ELECTRICAL		Luminous flux	1200 lm	Mounting type	In-ceiling installation
Mains connection	220...240 V / 50 – 60 Hz	Beam angle	70°	Colour	White
Power	15 W	Luminaire luminous efficacy	80 lm/W	SCOPE OF DELIVERY & WARRANTY	
Replaceable driver	Yes	Glare value	UGR < 19	Manufacturer warranty	5 years
Type of wiring	Ending	LIFETIME		CERTIFICATES & EPREL	
LED rated current	350 mA	LED lifespan (25 °C)	50000 h	EPREL energy efficiency class	F

fayola 100 DALI 4K

FAYOLA 100-205

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220185	fayola 125 DALI 4K	
 220186	fayola 150 DALI 4K	
 220187	fayola 175 DALI 4K	
 220188	fayola 205 DALI 4K	
 220721	Emergency Package 1h (50V/2.5W/Box)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.

220184

Typ

fayola 100 DALI 4K

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss